
NORTHERN KENTUCKY WATER DISTRICT KENTON COUNTY, KENTUCKY





TAYLOR MILL WATER TREATMENT PLANT ELECTRICAL AND BASIN IMPROVEMENTS


DRAWINGS FOR:
NKWD PROJECT NO. 184-0476
DOW LOAN NO. DWL 13060

JANUARY 2014



















NOT TO SCALE

BID SET

INDEX OF DRAWINGS

DWG NO	DESCRIPTION
SHEET NO.	GENERAL
G-00-001	COVER SHEET
G-00-002	INDEX OF DRAWINGS
G-00-003	NOTES, SYMBOLS, AND ABBREVIATIONS
SHEET NO.	MECHANICAL
M-01-001	FILTER BUILDING - FRONT PUMP ROOM AND BASEMENT MODIFICATION PLANS AND DETAILS
M-01-002	FILTER BUILDING - FRONT PUMP ROOM MODIFICATION SECTIONS
M-01-003	FILTER BUILDING - BACK PUMP ROOM MODIFICATION PLANS
M-01-004	FILTER BUILDING - BACK PUMP ROOM MODIFICATION SECTIONS
M-02-001	BASINS MODIFICATION PLAN AND SECTION
SHEET NO.	STRUCTURAL
S-00-001	GENERAL STRUCTURAL NOTES AND ABBREVIATIONS
S-02-001	OVERALL DEMOLITION PLAN
S-02-002	DEMOLITIONS SECTIONS
S-02-003	ENLARGED RAPID MIX, CHANNEL, AND TUNNEL PLANS
S-02-004	SECTIONS AND DETAIL
S-02-005	ENLARGED SEDIMENTATION BASIN PLANS
S-02-006	SECTIONS AND DETAILS
S-02-007	REPAIR DETAILS
S-02-008	TYPICAL DETAILS AND REPAIR SCHEDULE
SHEET NO.	ARCHITECTURAL
A-01-001	FILTER BUILDING DEMOLITION PLANS
A-01-002	FILTER BUILDING PLANS AT EL. 525.50 AND 535.00
A-01-003	FILTER BUILDING PLAN AT EL. 545.00, SECTION AND DETAILS
A-01-004	FILTER BUILDING ROOF PLAN AND SECTIONS
A-01-005	FILTER BUILDING ELEVATIONS
A-01-006	FILTER BUILDING SECTION AND DETAILS SHEET
SHEET NO.	HVAC
H-00-001	GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS
H-00-002	HVAC DETAILS
H-00-003	HVAC SCHEDULES
H-01-001	FILTER BUILDING PUMP ROOM HVAC PLANS AT EL. 525.50
H-01-002	FILTER BUILDING THIRD FLOOR AND PARTIAL ROOF HVAC PLANS
H-01-003	FILTER BUILDING MEZZANINE HVAC PLANS AT EL. 535.00
SHEET NO.	ELECTRICAL
E-00-001	GENERAL SYMBOLS AND ABBREVIATIONS
E-00-002	DETAILS AND SCHEDULES
E-00-003	POWER SYSTEM ONE LINE DIAGRAM
E-00-004	HIGH SERVICE PUMP CONTROL CIRCUITS I
E-00-005	HIGH SERVICE PUMP CONTROL CIRCUITS II
E-01-001	FILTER BUILDING ELECTRICAL PUMP ROOM DEMO. PLAN AT EL. 525.50
E-01-002	FILTER BUILDING ELECTRICAL MEZZANINE DEMO. PLAN AT EL. 535.00
E-01-003	FILTER BUILDING ELECTRICAL THIRD FLOOR DEMO. PLAN AT EL. 545.00
E-01-004	FILTER BUILDING POWER PLAN AT EL. 525.50
E-01-005	FILTER BUILDING PUMP ROOM POWER PLAN AT EL. 525.50
E-01-006	FILTER BUILDING MEZZANINE POWER PLAN AT EL. 535.00 I
E-01-007	FILTER BUILDING MEZZANINE POWER PLAN AT EL. 535.00 II
E-01-008	FILTER BUILDING THIRD FLOOR LIGHTING PLAN AT EL.545.00
E-01-009	FILTER BUILDING THIRD FLOOR POWER PLAN AT EL. 545.00 I
E-01-010	FILTER BUILDING THIRD FLOOR POWER PLAN AT EL. 545.00 II TUNNEL ELECTRICAL PLANS







			REVISIONS	·
NO.	BY	DATE	REMARKS	111
				DESJIL
				_{DWN} PJW
<u> </u>		·		·
				ovo JMA
				CKD

NORTHERN KENTUCKY WATER DISTRICT
TAYLOR MILL WATER TREATMENT PLANT

ELECTRICAL AND BASIN IMPROVEMENTS

GENERAL
INDEX OF
DRAWINGS
SCALE: NO SCALE


ISSUED STATUS: BID SET


DATE JANUARY 2014

SHEET G-00-002

CAD REF. NO. 2142001.0002

TYPICAL SECTION/ ELEVATION TAGS





TITLE ALL CAPS

TYPICAL DETAIL TAG




DETAIL INDICATOR




DETAIL INDICATOR



DETAIL INDICATOR WITH AREA




TYPICAL PHOTO TAG




— PHOTO IS LOCATED


SHEET # ON WHICH

- PHOTO IS REFERRED TO FIRST





HMagna



REVISIONS NO. BY DATE DWN PJW T CKD JMA

TYPICAL NOTE TAG

○ SHEET KEYNOTES:

1. KEYNOTES

GENERAL NOTES:

1. GENERAL NOTES

TYPICAL NORTH SYMBOL



NORTH ARROW

MECHANICAL ABBREVIATIONS

AB	ANCHOR BOLT	EA.	EACH	MGD	MILLION GALLONS PER DAY
		ECC	ECCENTRIC	МН	MANHOLE
ABAN.	ABANDONED	EDB	ELECTRICAL DUCT BANK	MIN.	MINIMUM
AC	ASPHALT CONCRETE PAVEMENT	EF	EACH FACE	MIPT	MALE IRON PIPE THREAD
ADD'L.	ADDITIONAL			MJ	MECHANICAL JOINT
ADJ.	ADJUSTABLE	EFF.	EFFLUENT		
AH	ACCESS HATCH	EJ	EXPANSION JOINT	MO	MASONRY OPENING
ALUM.	ALUMINUM	EL.	ELEVATION	NC	NORMALLY CLOSED
ALT.	ALTERNATE	ELEC.	ELECTRIC	NF	NEAR FACE
ARCH	ARCHITECTURE	EMH	ELECTRICAL MANHOLE	NO	NORMALLY OPEN
BF	BLIND FLANGE	EQ.	EQUALIZATION	NO.	NUMBER
		EW	EACH WAY	0	OVERFLOW
BFV	BUTTERFLY VALVE	EX.	EXISTING	OC	ON CENTER
BITUM.	BITUMINOUS			OD	OUTSIDE DIAMETER
BL	BASELINE	FD	FLOOR DRAIN		OUTSIDE BIAMETER
BLDG.	BUILDING	FDN	FOUNDATION	OF	
BM	BENCH MARK	FDND	FOUNDATION DRAIN	OPNG.	OPENING
BM.	BEAM	FF	FAR FACE	OPP.	OPPOSITE
BOP	BOTTOM OF PIPE	FIN.	FINISHED	PC .	POINT OF CURVATURE
BOT.	BOTTOM	FIPT	FEMALE IRON PIPE THREAD	PE	PLAIN END
BRG	BEARING	FLEX.	FLEXIBLE	Pl	POINT OF INTERSECTION
	BUILDING REFERENCE POINT	FLG.	FLANGE	PL	PLATE OR PROPERTY LINE
BRP		FLR.	FLOOR	PSF	POUNDS PER SQUARE FOOT
BW [*]	BACKWASH			PSI	POUNDS PER SQUARE INCH
BWS	BACKWASH SUPPLY	FTG.	FOOTING		POINT OF TANGENCY
₽ WW С	BACKWASH WASTE	FT., '	FEET	PT	
Ć '	CENTERLINE	GA.	GAGE OR GAUGE	R	RISER
C/C	CENTER TO CENTER	GAC	GRANULAR ACTIVATED CARBON	RED.	REDUCER
СВ	CATCH BASIN	GALV.	GALVANIZED	REINF.	REINFORCEMENT OR REINFORCE
CHEM	CHEMICAL LINE	GE	GROOVED END JOINT	REQ'D.	REQUIRED
CHH	COMMUNICATION HANDHOLE	GRD.	GROUND	RMJ	RESTRAINED JOINT
	CONSTRUCTION JOINT	GRAT.	GRATING	RM.	ROOM
Cl		HB	HOSE BIB	ROW	RIGHT OF WAY
CL.	CLEAR		HARNESSED FLANGE COUPLING ADAPTER	RPCV	ROTARY PUMP CONTROL VALVE
CMH	COMMUNICATION MANHOLE	HFCA		SHT.	SHEET
CMU	CONCRETE MASONRY UNIT	HORIZ.	HORIZONTAL		
CO	CLEANOUT	HP	HIGH POINT	SOC	SOCKET
COL.	COLUMN	ID	INSIDE DIAMETER	SPA.	SPACING
CONC.	CONCRETE	IF	INSIDE FACE	SR	SHORT RADIUS
CONN	CMU CORNER OF EXT. FACE	IN., "	INCHES	SS	STAINLESS STEEL
CONT.	CONTINUED	INF.	INFLUENT	STD.	STANDARD
		INV.	INVERT	STL.	STEEL
CPLG.	COUPLING	JST.	JOIST	STRUC.	STRUCTURAL
CTW	CONTACTOR TO WASTE	JT.	JOINT	T	TREAD
CY	CUBIC YARD(S)			T/	TOP OF
CW	COLD WATER (POTABLE)	K	KIP (1000 POUNDS)		TOP AND BOTTOM
D	DRAIN	KSF	KIPS PER SQUARE FOOT	T&B	
DET.	DETAIL	LG.	LONG	THK.	THICK
DIP	DUCTILE IRON PIPE	LLH	LONG LEG HORIZONTAL	TYP.	TYPICAL
DIA.	DIAMETER	LLV	LONG LEG VERTICAL	UON	UNLESS OTHERWISE NOTED
DIM	DIMENSION	LR	LONG RADIUS	USG	UNITED STATES STANDARD GAGE
	DISCHARGE	LSH	LEVEL SWITCH HIGH	VERT:	VERTICAL
DISCH.	DROP MANHOLE	LSLL	LEVEL SWITCH LOW LOW	W/	WITH
DMH		MAS	MASONRY	WP	WORK POINT
DN.	DOWN	MAX.		WRF	WATER RECLAMATION FACILITY
DTL	DETAIL		MAXIMUM	WS	WATER STOP
DWGS	DRAWINGS	MCC	MOTOR CONTROL CENTER		WELDED WIRE FABRIC
DWL.	DOWELS	MFR.	MANUFACTURER	WWF	WELDED WINE PADRIC

IDENTIFYING LETTERS FOR GROUP OF DRAWINGS

ELECTRICAL

TMTP AREA LEGEND

AREA DESCRIPTION NUMBER GENERAL SHEETS FILTER BUILDING SEDIMENTATION BASINS

DIMENSIONS:

DENOTES DIMENSIONS TO BE DETERMINED BY MANUFACTURER

DENOTES DIMENSIONS TO BE CONTRACTOR.


NORTHERN KENTUCKY WATER DISTRICT TAYLOR MILL WATER TREATMENT PLANT


ELECTRICAL AND BASIN **IMPROVEMENTS**

GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS ISSUED STATUS: BID SET JANUARY 2014

G-00-003 CAD REF. NO. 2142001.003

SCALE: NO SCALE






1ST FLOOR PLAN


1. CONTRACTOR SHALL PROVIDE AND INSTALL 1/4" GALVANIZED, PAINTED COVER PLATE OVER EXISTING OPENING. CONTRACTOR SHALL VERIFY SIZE REQUIRED. PAINTING AND ANCHOR HARDWARE PER CONTRACT DOCUMENTS.

- 2. CONTRACTOR SHALL CONNECT EACH RPCV TO ASSOCIATED EXISTING PVC DRAIN LINE AS REQUIRED.
- 3. DIMENSIONS MARKED WITH "**" SHALL BE DETERMINED IN FIELD BY CONTRACTOR. CONTRACTOR SHALL PROVIDE ANY ADDITIONAL PIPING, FITTINGS AND SPECIALTIES AS REQUIRED TO ASSEMBLE DISCHARGE PIPING.
- WORK WITHIN THIS BOUNDARY LINE IS PART OF ALTERNATIVE NO. 2. SEE SPECIFICATION SECTION 01 23 00 FOR DESCRIPTION OF ALTERNATIVE NO. 2.



TYPICAL PIPE/VALVE SUPPORT DETAIL

- 2. COORDINATE LOCATION OF PIPE SUPPORTS WITH M SHEETS AND SPECIFICATIONS.



PUMP NO. 3 AIR VALVE DETAIL

AS REQUIRED OR AS SHOWN ON THE WELDED BRACKET -- ANCHOR IN ACCORDANCE WITH THE SPECIFICATIONS

WALL BRACKET DETAIL



1.	CONTRACTOR SHALL REN	MOVE AND REPLACE BUTT	ERFLY	VALVES	·			
					,	REVISIONS		_
nic	OF KENSON		NO.	BY	DATE	REMARKS	DE0	JIL
	Series Ochery						DES	
ADIS	* ABBOTT 2						ł	D 11/4/
	PR 25937 *						DWN	_PJW
	CENSED						1	
	ONAL ENGINEER						CKD	JMA
S	12-1/21/21/21/3							


NORTHERN KENTUCKY WATER DISTRICT TAYLOR MILL WATER TREATMENT PLANT ELECTRICAL AND BASIN


IMPROVEMENTS

FILTER BUILDING FRONT PUMP ROOM AND BASEMENT MODIFICATION PLANS AND DETAILS

ISSUED STATUS: BID SET JANUARY 2014 M-01-001

CAD REF. NO. M-01-001.DWG





EL. 510.17± PUMP NO. 1 SECTION (M-01-001) NOT TO SCALE

- 20" BFV

20" WYE

20" 45° BEND

SUPPORT (TYP.)

20" FLGxFLG


20" SUCTION LINE


QEL. 514.00±

WALL PIPE

1. CONTRACTOR SHALL COORDINATE WITH PUMP MANUFACTURER TO PROVIDE / INSTALL REQUIRED TRANSITION PLATE FOR INSTALLATION OF NEW PUMP ONTO EXISTING CAN.

2. DIMENSIONS MARKED WITH A "±" SHALL BE COORDINATED BY CONTRACTOR WITH PUMP MANUFACTURER AND FIELD VERIFIED.





PUMP NO. 3 DEMO SECTION M-01-001

NORTHERN KENTUCKY WATER DISTRICT TAYLOR MILL WATER TREATMENT PLANT

ELECTRICAL AND BASIN **IMPROVEMENTS**

FILTER BUILDING FRONT PUMP ROOM MODIFICATION SECTIONS SSUED STATUS: BID SET JANUARY 2014

3. WORK SHOWN WITHIN THIS BOUNDARY LINE IS PART OF ALTERNATIVE

ALTERNATIVE NO. 2.

M-01-002 CAD REF. NO. _____M-01-002.DWG


ARCADIS |

DRAWING IS NOT TO SCALE IF THIS DOES NOT





REVISIONS NO. BY DATE _{DWN}___PJW_ CKD ____JMA

SCALE: N.T.S




2. CONTRACTOR SHALL DEMOLISH BEND, PIPING, AND BASE PLATE. CONCRETE PAD TO REMAIN.





- 1. CONTRACTOR SHALL PROVIDE AND INSTALL 1/4" STEEL PAINTED COVER PLATE FOR EXISTING OPENING. CONTRACTOR SHALL VERIFY SIZE REQUIRED. PAINTING AND ANCHOR HARDWARE PER CONTRACT DOCUMENTS.
- 2. CONTRACTOR SHALL MODIFY PUMP DISCHARGE PIPING, VALVES, FITTINGS, AND APPURTENANCES AS REQUIRED FOR INSTALLATION OF NEW PUMPS.



CLEARWELL PLAN

/ NOT TO SCAL

- ES. DIMENSIONS MARKED WITH A "±" SHALL BE COORDINATED BY CONTRACTOR WITH PUMP MANUFACTURER AN FIELD VERIFIEI
- 2. DIMENSIONS MARKED WITH "**" SHALL BE DETERMINED IN FIELD BY CONTRACTOR. CONTRACTOR SHALL PROVIDE ANY ADDITIONAL PIPING, FITTINGS AND SPECIALT AS REQUIRED TO ASSEMBLE SUCTION PIPING, WHEN POSSIBLE, CONTRACTOR SHALL PROVIDE DISMANTLING JOINT.






ı				REVISIONS	
ı	NO.	BY	DATE	REMARKS	n=0
١					DESJIL
ı					
I			1		DWNPJW
ı					
۱					INAA
ı					CKDJMA


NORTHERN KENTUCKY WATER DISTRICT TAYLOR MILL WATER TREATMENT PLANT

ELECTRICAL AND BASIN IMPROVEMENTS

FILTER BUILDING
BACK PUMP ROOM
MODIFICATION PLANS

SCALE: N.T.S.





- 2. THE SYMBOLS, ABBREVIATIONS, AND LAP SPLICE AND EMBEDMENT TABLE ON THIS SHEET IS A COMPREHENSIVE STANDARD GUIDE FOR GENERAL USE ON ALL PROJECTS. THEREFORE NOT ALL THE SYMBOLS AND ABBREVIATIONS CONTAINED IN THIS LIST ARE NECESSARILY USED ON THIS PARTICULAR PROJECT AND SHOULD BE USED FOR CLARIFICATION ONLY.
- 3. QUALITY OF CONSTRUCTION REQUIRED, PERFORMANCE LEVELS OF WORKMANSHIP, MANUFACTURING AND INDUSTRY STANDARDS, STRENGTH AND PHYSICAL REQUIREMENTS OF MATERIALS, CONFORMANCE TO CODES AND REGULATIONS, GUARANTEES AND OTHER PROJECT REQUIREMENTS ARE SPECIFIED IN THE PROJECT MANUAL.
- 4. IF MATERIALS, QUANTITIES, STRENGTHS OR SIZES INDICATED BY THE DRAWINGS OR SPECIFICATIONS ARE NOT IN AGREEMENT WITH THESE NOTES, THE BETTER QUALITY AND/OR GREATER QUANTITY, STRENGTH OR SIZE INDICATED, SPECIFIED, OR NOTED SHALL BE PROVIDED.
- 5. PERFORM ALL WORK IN COORDINATION WITH ALL DRAWINGS AND INFORMATION RELATED TO STRUCTURAL WORK. ANY CHANGES TO THE EQUIPMENT REQUIRING CHANGES TO THE STRUCTURAL SYSTEMS SHALL BE REDESIGNED BY A PROFESSIONAL ENGINEER REGISTERED IN THE STATE OF KENTUCKY AT NO COST TO THE OWNER AND SUBMITTED TO THE ENGINEER. SUBMITTAL SHALL BE ACKNOWLEDGED IN WRITING BEFORE BEGINNING CONSTRUCTION.
- 6. IT IS SOLELY THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE ERECTION PROCEDURE AND SEQUENCE TO ENSURE THE SAFETY OF THE STRUCTURE AND ITS COMPONENT PARTS DURING ERECTION. THIS INCLUDES, BUT IS NOT LIMITED TO, THE ADDITION OF WHATEVER TEMPORARY BRACING, GUYS OR TIE-DOWNS MAY BE NECESSARY. SUCH MATERIAL SHALL BE REMOVED AND SHALL REMAIN THE PROPERTY OF THE CONTRACTOR AFTER COMPLETION OF THE PROJECT.
- 7. FACILITIES HAVE BEEN DESIGNED FOR DESIGN LOADS SHOWN OR SPECIFIED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FACILITIES SUBJECT TO CONSTRUCTION LOADS EXCEEDING THE DESIGN LOADS AND SHALL NOTIFY THE ENGINEER OF ANY SUCH ADDITIONAL LOADS.
- 8. ALL DIMENSIONS AND ELEVATIONS NOTED THUS (*) ON STRUCTURES SHOWN ON THE DRAWINGS SHALL BE VERIFIED BY THE CONTRACTOR IN THE FIELD OR WITH THE EQUIPMENT MANUFACTURER AND SHALL CONFORM TO THOSE SHOWN ON OTHER DRAWINGS.
- DESIGN LOADS: BASED ON THE KENTUCKY BUILDING CODE, 2007 EDITION.
 - FLOOR LIVE LOADS: - SEE PLANS

SNOW LOAD:

- GROUND SNOW LOAD, Pg	20 PS
- SNOW EXPOSURE FACTOR	0.9
- SNOW LOAD IMPORTANCE FACTOR:	1.1
- THERMAL FACTOR	1.1

WIND LOAD:

- BASIC WIND SPEED	90 MP
- WIND IMPORTANCE FACTOR:	1.15
- WIND EXPOSURE	С
- COMPONENTS AND CLADDING (SEE SPECI	FICATIONS)

EARTHQUAKE DESIGN DATA:

- SEISMIC IMPORTANCE FACTOR:	1.25
- OCCUPANCY CATEGORY	111
- SPECTRAL RESPONSE ACCELERATIONS, Ss	0.18
- SPECTRAL RESPONSE ACCELERATIONS, S1	0.07
- SITE CLASS	D
- SPECTRAL RESPONSE COEFFICIENT, Sos	0.14
- SPECTRAL RESPONSE COEFFICIENT, Son	0.08
- SEISMIC DESIGN CATEGORY	В

10. FOR PAINTING SYSTEM REQUIREMENTS REFER TO SPECIFICATION SECTION 09 91 00.

CAST-IN-PLACE CONCRETE

- CONCRETE SHALL HAVE THE FOLLOWING MINIMUM COMPRESSIVE STRENGTH AT 28 DAYS:
- A. 4,500 POUNDS PER SQUARE INCH (PSI) WITH ENTRAINED AIR FOR ALL CONCRETE UNLESS SPECIFICALLY NOTED OTHERWISE.
- 2. ALL CONCRETE WORK NOT COVERED UNDER ACI 350 SHALL BE IN ACCORDANCE WITH "THE BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE" ACI 318. TOLERANCES SHALL BE IN ACCORDANCE WITH ACI 347, SECTION 3.3.1, TOLERANCES FOR REINFORCED CONCRETE BUILDINGS.
- 3. ALL REINFORCING STEEL SHALL BE NEW DOMESTIC DEFORMED BILLET STEEL CONFORMING TO ASTM A-615 GRADE 60.
- 4. ALL REINFORCING DETAILS SHALL CONFORM TO "DETAILS AND DETAILING OF CONCRETE REINFORCEMENT", ACI 315, UNLESS DETAILED OTHERWISE ON THE STRUCTURAL DRAWINGS.
- CONTRACTOR SHALL REVIEW ALL DRAWINGS FOR SIZE AND LOCATION OF EMBEDDED ITEMS, SLEEVES, SLAB DEPRESSIONS, REQUIRED. THESE ITEMS SHALL BE FURNISHED AND INSTALLED PRIOR TO PLACEMENT OF CONCRETE.
- ALL BEAMS, SPANDRELS AND SLABS SHALL BE CAST MONOLITHICAL-LY, EXCEPT FOR REQUIRED CONSTRUCTION JOINTS. CONTRACTOR SHALL SUBMIT ANY AND ALL ALTERNATE AND ADDITIONAL CON-STRUCTION JOINT LOCATIONS AND DETAILS.
- 7. CONSTRUCTION JOINTS REQUIRED BY THE ENGINEER ARE SHOWN ON THE DRAWINGS. ADDITIONAL CONSTRUCTION JOINTS SHALL BE PROVIDED AS OUTLINED IN SPECIFICATIONS. REINFORCEMENT SHALL BE CONTINUOUS ACROSS CONSTRUCTION JOINTS. SUBMIT ALL CONSTRUCTION JOINT LOCATIONS WITH REINFORCING STEEL SHOP DRAWINGS.
- CONTRACTOR SHALL PROVIDE 3/4 INCH CHAMFER USING WOOD CHAMFER STRIPS ON ALL EXPOSED CORNERS OF COLUMNS, BEAMS AND WALLS, OR AS REQUIRED TO MATCH EXISTING.
- 9. COVER FOR REINFORCING STEEL SHALL CONFORM TO THE FOLLOWING:

TYPICAL REINFORCING BAR COVER TABLE	
CONCRETE CAST AGAINST EARTH	3"
REINFORCING TO CLEAR WATERSTOP	.3"
SURFACES EXPOSED TO LIQUIDS, EARTH OR WEATHER	2"

ALL OTHER SURFACES 2'


- 10. PROVIDE WATERSTOPS IN ALL FOUNDATIONS, TANKS AND OTHER SUBSTRUCTURES UP TO AN ELEVATION AT LEAST 12 INCHES ABOVE GRADE OR TO AN ELEVATION AT LEAST 12 INCHES ABOVE LIQUID LEVEL IN TANKS, WHICHEVER IS HIGHER, UNLESS SHOWN OTHERWISE
- 11. CALCIUM CHLORIDE SHALL NOT BE PERMITTED NOR SHALL ANY ADMIXTURE CONTAINING CALCIUM CHLORIDE BE PERMITTED THAT RESULTS IN A TOTAL CONCRETE MIX IN WHICH THE PRESENCE OF CHLORIDE IONS EXCEED 0.10 PERCENT BY WEIGHT OF CEMENT.
- 12. ALUMINUM PIPE SHALL NOT BE USED WITH CONCRETE PUMPS.
- 13. CONTRACTOR SHALL LOCATE ALL EXISTING REINFORCING PRIOR TO INSTALLING ADHESIVE DOWELS AND ADHESIVE AND MECHANICAL ANCHORS. CONTRACTOR SHALL USE X-RAY TYPE NON-DESTRUCTIVE INSPECTION METHOD.


SPECIAL INSPECTION


- OWNER WILL RETAIN THE INSPECTION SERVICES FOR SPECIAL INSPECTION. ON SITE INSPECTION WILL BE IN ACCORDANCE TO THE KENTUCKY BUILDING CODE SECTION 17 REGULATIONS UNDER THE SUPERVISION OF A QUALIFIED INSPECTOR.
- 2. TESTING SERVICES SHALL BE PERFORMED AS STIPULATED BY THE
- 3. CONTRACTOR SHALL NOTIFY INSPECTION AT LEAST 48 HOURS PRIOR TO THE


EXISTING CONCRETE

- EXISTING MATERIAL PROPERTIES UTILIZED FOR ANALYSIS:
 CONCRETE COMPRESSIVE STRENGTH = 3,000 PSI
 REINFORCING STEEL YIELD STRENGTH = 40,000 PSI
- 2. EXISTING CONCRETE REFERS TO CONCRETE WHICH IS IN PLACE PRIOR TO THE START OF THIS PROJECT.
- 3. PRIOR TO BEGINNING DEMOLITION WORK OF EXISTING CONCRETE PROVIDE ALL NECESSARY TEMPORARY SUPPORTS AND LOCATE AND PROTECT ALL ELECTRICAL CONDUITS AND PIPES AS OUTLINED IN SPECIFICATIONS.
- REMOVE EXISTING CONCRETE GENERALLY WITHIN THE LIMITS SHOWN ON THE DRAWINGS.
- 5. WHERE EXISTING REINFORCING IS SHOWN ON THE DESIGN DRAWINGS AS PROJECTING INTO NEW CONCRETE WORK, THE EXISTING REINFORCING SHALL PROJECT INTO THE NEW CONCRETE THE MINIMUM LAP LENGTH AS NOTED IN THE "LAP SPLICE AND EMBEDMENT LENGTH TABLE". REMOVE ALL FOREIGN MATERIAL FROM SURFACE OF EXISTING REINFORCING WITH A WIRE BRUSH OR OTHER MEANS.
- 6. WHERE NEW REINFORCING DOWELS ARE SHOWN TO BE EMBEDDED INTO THE EXISTING CONCRETE, THE NEW DOWELS SHALL BE INSTALLED INTO INTO THE DEPTH OF HOLE NOTED OR REQUIRED TO FULLY DEVELOP THE TENSILE STRENGTH OF THE REINFORCING BAR. USE ADHESIVE MATERIAL, HOLE DIAMETERS AND DEPTH, AND INSTALLATION PROCEDURES AS REQUIRED BY THE MANUFACTURER AND OUTLINED IN SPECIFICATIONS.
- WHERE NEW REINFORCING DOWELS ARE PROPOSED BY CONTRACTOR TO REPLACE CUT OR DAMAGED EXISTING REINFORCING, SUBMIT LOCATIONS AND DEPTHS FOR APPROVAL PRIOR TO COMMENCEMENT OF WORK.
- 8. PROVIDE CHAMFERS ON NEW CONCRETE WORK WHERE REQUIRED TO MATCH CHAMFERS ON EXISTING CONCRETE WORK.
- 9. WHERE REQUIRED TO SECURE BACKFILLED MATERIAL OR MAKE EXISTING CONCRETE WATERTIGHT, FILL ALL ABANDONED PIPE SLEEVES, AND OTHER OPENINGS WITH NON-SHRINK GROUT.
- 10. AFTER REMOVAL OF PART OR ALL OF EXISTING CONCRETE WORK, WHICH TIES INTO NEW OR EXISTING WORK, THE EXPOSED AREAS OF THE EXISTING WORK SHALL BE NEATLY REPAIRED AS OUTLINED IN SPECIFICATIONS. PROPERLY CLEAN AND ROUGHEN SURFACE AND APPLY BONDING ADHESIVE PRIOR TO PLACING THE SPECIFIED SPECIFIED CONCRETE SURFACE REPAIR MATERIAL.
- 11. WHERE DEMOLITION OF EXISTING STRUCTURES IS PERFORMED, IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO MAINTAIN THE INTEGRITY OF ADJACENT STRUCTURES AND TO PREVENT DAMAGE TO EXISTING FACILITIES AND EQUIPMENT.










135° HOOK

REINFORCEMENT LAP SPLICE, EMBEDMENT LENGTH AND STANDARD HOOKS TABLE IS BASED ON A MINIMUM CONCRETE COMPRESSIVE STRENGTH OF 4000 PSI AND 60000 PSI REINFORCEMENT (WITH NO EPOXY COATING).

ALL LAPS SPLICES SHALL BE CLASS B SPLICES.


- * THE MINIMUM LAP LENGTH FOR BEAMS, COLUMNS, AND STRAIGHT EMBEDMENTS ARE BASED ON A 3 BAR DIAMETER MINIMUM CENTER TO CENTER BAR SPACING AND A 2 INCH BAR COVER. IF THE SPLICE AND/OR EMBEDMENT DOES NOT CONFORM TO THESE REQUIREMENTS, THEN CONTRACTOR SHALL APPLY APPROPRIATE FACTORS IN COMPLIANCE WITH ACI 318 WITH APPROVAL BY ENGINEER.
- ** THE MINIMUM LAP LENGTH FOR SLABS, WALLS, AND STRAIGHT EMBEDMENTS ARE BASED ON A 6 INCH BAR SPACING AND A 2 INCH BAR COVER. IF THE LAP CONDITION DOES NOTE CONFORM TO THESE REQUIREMENTS, THEN USE BEAM LAP LENGTHS; OR COMPLY WITH LAP REQUIREMENTS OF ACI 318 WITH APPROVAL BY ENGINEER.
- *** TOP BARS ARE DEFINED AS ALL HORIZONTAL BARS, EXCLUDING WALL BARS, WITH 12" OR MORE FRESH CONCRETE BENEATH.
- WHERE SPLICES ARE REQUIRED BETWEEN BARS OF DIFFERENT SIZES, THE LAP LENGTH SHALL BE NO LESS THAN THE EMBEDMENT LENGTH OF THE LARGER BAR OR THE LAP LENGTH OF THE SMALLER BAR, WHICHEVER IS GREATER.

LAP SPLICE AND EMBEDMENT LENGTH TABLE



DRAWING IS
NOT TO SCALE
IF THIS DOES NOT
MEASURE 1 INCH.





				REVISIONS		
	NO.	BY	DATE	REMARKS	DES _	JH
,					DWN	JJH
					CKD	IVC
		 				

NORTHERN KENTUCKY WATER DISTRICT TAYLOR MILL WATER TREATMENT PLANT

ELECTRICAL AND BASIN IMPROVEMENTS

STRUCTURAL

GENERAL STRUCTURAL NOTES, AND ABBREVIATIONS


SCALE: N.T.S.

DATE ______JANUARY 2014

SHEET ______S-00-001

CAD REF. NO. ____2142001S01

ISSUED STATUS: BID SET



- 1. REMOVE AND RE-INSTALL AFTER CONCRETE WORK IS
- 2. FOR PLAN DIMENSIONS SEE SHEETS 003 AND 005.

** REMOVE DETERIORATED CONCRETE DOWN TO SOUND CONCRETE. LIMITS PROVIDED ARE FOR BID PURPOSES AND MAY BE ADJUSTED FOR REMOVAL. ADJUSTMENTS SHALL NOT OCCUR WITHOUT THE ENGINEER'S APPROVAL.

DRAWING IS NOT TO SCALE IF THIS DOES NOT MEASURE 1 INCH.



22541

REVISIONS JJH IVC

NORTHERN KENTUCKY WATER DISTRICT TAYLOR MILL WATER TREATMENT PLANT ELECTRICAL AND BASIN

IMPROVEMENTS


STRUCTURAL OVERALL DEMOLITION PLAN


JANUARY 2014


SCALE: 1/8" = 1'-0"


S-02-001 CAD REF. NO. 2142001S02


ISSUED STATUS: BID SET














GENERAL NOTE:

** LIMITS PROVIDED FOR CONCRETE REPLACEMENT ARE FOR BID PURPOSES AND MAY BE ADJUSTED DURING THE WORK. ADJUSTMENTS SHALL NOT OCCUR WITHOUT ENGINEER'S APPROVAL.

MARCOLM GARCADIS

The Water Division of ARCADIS

Electrical - Mechanical - Indian consumption of Engineers



			REVISIONS		
NO.	BY	DATE	REMARKS		JH
				DES	JI
<u></u>					
				DWN	JJI
				İ	
				CKD	IVO
				OND	

NORTHERN KENTUCKY WATER DISTRICT
TAYLOR MILL WATER TREATMENT PLANT

ELECTRICAL AND BASIN IMPROVEMENTS


STRUCTURAL
SECTIONS AND DETAILS

SCALE: 3/8" = 1'-0"



KEYED NOTES


- 1 REMOVE EXISTING EXPANSION JOINT MATERIAL AND RECONSTRUCT JOINT AS DIRECTED BY ENGINEER IN ACCORDANCE TO SPALL REPAIR DETAIL.
- 2 PLACE BACKER ROD SOAKED IN CRACK INJECTION REPAIR SYSTEM HYDROPHOBIC POLYURETHANE CHEMICAL GROUT.
- 3 INSTALL EXPANSION JOINT REPAIR SYSTEM, HYPALON SHEETING SHALL BE INSTALLED TO ALLOW FOR 3/4" MOVEMENT WITHOUT INDUCING TENSION INTO HYPALON.
- 4 1/2 THICKNESS OF JOINT.
- 5 REMOVE EXISTING EXPANSION JOINT MATERIAL AS NECESSARY TO INSTALL BACKER ROD DOWN TO TOP OF
- 6 JOINT SEALER.



CONCRETE REMOVAL AND REPLACEMENT

KEYED NOTES


- REMOVE EXISTING CONCRETE USING HYDRODEMOLITION METHODS AS REQUIRED. DO NOT CUT OR DAMAGE EXISTING REINFORCING DURING CONCRETE REMOVAL PROCESS.
- 2 REMOVE ALL DETERIORATED CONCRETE TO SOUND CONCRETE. PREPARE CONCRETE SUBSTRATE TO OBTAIN A SURFACE PROFILE OF 1/8-INCH IN DEPTH WITH A NEW FRACTURED AGGREGATE SURFACE.
- WHERE REINFORCING STEEL WITH ACTIVE CORROSION IS ENCOUNTERED. REPLACEMENT IS REQUIRED WHERE LOSS ON REBAR CROSS SECTION IS OVER 25%. AFTER REPAIR WHERE REINFORCING REMAINS, CLEAN REINFORCING STEEL TO REMOVE ALL CONTAMINANTS AND RUST.
- IF REINFORCING REPLACEMENT IS REQUIRED, CUT EXISTING CORRODED REINFORCING BAR AS REQUIRED AND WELD NEW REBAR OF SAME SIZE, AS SHOWN.
- (5) SURFACE PREPARATION SHALL COMPLY WITH BONDING AGENT AND REPAIR MORTAR MANUFACTURER'S INSTRUCTIONS.
- (6) INSTALL CONCRETE PER PROJECT SPECIFICATION 03 00 05.
- (7) FOR BID PURPOSES, TOTAL DEPTH OF REPAIR IS EQUAL TO
- 8 S, (E), AND L1 DEFINITIONS CORRESPOND TO ANSI/AWS D1.4. MINIMUM L1 FOR BIDDING PURPOSES IS 3 INCHES.



CRACK REPAIR

KEYED NOTES

- (1) LEAKING CRACK
- INJECTION PORTS FOR HYDROPHILIC CRACK INJECTION MATERIAL.




CONCRETE SURFACE SPALL


KEYED NOTES

- SCORE-CUT PERIMETER OF REPAIR AREA AS GENERALLY SHOWN. DO NOT CUT REINFORCING UNLESS NECESSARY TO REMOVE ALL DETERIORATED CONCRETE.
- REMOVE ALL DETERIORATED CONCRETE TO SOUND CONCRETE. CHIP CONCRETE SUBSTRATE TO OBTAIN A SURFACE PROFILE OF 1/8-INCH IN DEPTH WITH A NEW FRACTURED AGGREGATE SURFACE.
- WHERE REINFORCING STEEL WITH ACTIVE CORROSION IS ENCOUNTERED. REPLACEMENT IS REQUIRED WHERE LOSS ON REBAR CROSS SECTION IS OVER 25%. AFTER REPAIR WHERE REINFORCING REMAINS, CLEAN REINFORCING STEEL TO REMOVE ALL CONTAMINANTS AND RUST. REMOVE CONCRETE TO A DEPTH OF 1-INCH MINIMUM BEHIND REINFORCING BAR AS SHOWN.
- IF REINFORCING REPLACEMENT IS REQUIRED, CUT EXISTING CORRODED REINFORCING BAR AS REQUIRED AND WELD NEW REBAR OF SAME SIZE, AS SHOWN.
- SURFACE PREPARATION SHALL COMPLY WITH REPAIR MORTAR MANUFACTURER'S INSTRUCTIONS.
- 6 INSTALL BONDING AGENT AND REPAIR MORTAR PER THE MANUFACTURER'S REQUIREMENTS.
- 7 FOR BID PURPOSES, ASSUME TOTAL DEPTH OF REPAIR IS 6 INCHES.
- 8 S, (E), AND L1 DEFINITIONS CORRESPOND TO ANSI/AWS D1.4. MINIMUM L1 FOR BIDDING PURPOSES IS 3 INCHES.

DRAWING IS NOT TO SCALE IF THIS DOES NOT MEASURE 1 INCH.







NORTHERN KENTUCKY WATER DISTRICT TAYLOR MILL WATER TREATMENT PLANT


ELECTRICAL AND BASIN **IMPROVEMENTS**


STRUCTURAL REPAIR DETAILS


SCALE: N.T.S.

ISSUED STATUS: BID SET JANUARY 2014 SHEET ___S-02-007

CAD REF. NO. 2142001S08











			REVISIONS		
NO.	BY	DATE	REMARKS	DES _	SRZ
				DWN_	JJH
			· · · · · · · · · · · · · · · · · · ·		
				CKD	IVC
				,	

NORTHERN KENTUCKY WATER DISTRICT TAYLOR MILL WATER TREATMENT PLANT

ELECTRICAL AND BASIN **IMPROVEMENTS**

ARCHITECTURAL FILTER BUILDING **DEMOLITION PLANS**

SCALE: 1/8" = 1'-0"

ISSUED STATUS: BID SET JANUARY 2014 A-01-001

GENERAL NOTES:

TO REMAIN.

TO THE OWNER.

#KEYNOTES:

FLUSH WITH EXISTING FLOOR.

SHEET A-01-005.

1. REMOVE GLAZING AND SPANDREL PANELS

INSTALLATION OF LOUVERS MECHANICAL LOUVERS. COORDINATE DEMOLITION WITH


2. REMOVE ELECTRICAL EQUIPMENT, SEE SHEET E-01-002. REMOVE EQUIPMENT SUPPORT RAILS


FROM WINDOW WALL SYSTEM AS REQUIRED FOR

1. CONTRACTOR SHALL PROTECT ALL EXISTING

2. PROVIDE TEMPORARY DUST BARRIERS AND WEATHER PROOF ENCLOSURES ACCEPTABLE

CAD REF. NO. _____A-01-001






GENERAL NOTES:

CONTRACTOR SHALL PROTECT ALL EXISTING TO REMAIN.

PROVIDE TEMPORARY DUST BARRIERS AND
 WEATHER PROOF ENCLOSURES ACCEPTABLE TO
 THE OWNER.


#KEYNOTES:

- LOUVERS, SEE DRAWINGS A-01-005 AND A-01-006.
 HVAC EQUIPMENT SEE "H" DRAWINGS.
- 3. INSTALL TERRAZZO FLOORING AT EXISTING
 CONCRETE SLAB TO MATCH EXISTING TERRAZZO
 FLOORING. APPROX 90 SF.
- PROVIDE METAL PANEL CEILING TO MATCH EXISTING WHERE ELECTRICAL ENCLOSURE WAS REMOVED. APPROX 90 SF.
- 5. PROVIDE METAL WALL PANEL TO MATCH EXISTING.










NORTHERN KENTUCKY WATER DISTRICT TAYLOR MILL WATER TREATMENT PLANT ELECTRICAL AND BASIN

IMPROVEMENTS

FILTER BUILDING PLANS AT EL. 525.50 AND 535.00

SCALE: 1/8" = 1'-0"



NOTE:

FLOOR LIVE LOAD = 250 PSF

BUILDING CODE SUMMARY EXISTING FILTER BUILDING

EXISTING BUILDING - NEW DEMOLITION PATCHING AT WALLS, MECHANICAL, AND ELECTRICAL WORK ONLY. WORK WILL NOT AFFECT MAXIMUM EXIT TRAVEL DISTANCE.

USE GROUP - CHAPTER 3

USE GROUP DESIGNATION

DESCRIPTION

FACTORY INDUSTRIAL, LOW

F-2

N.A.

HAZARD, PROCESSING BEVERAGES

BUILDING HEIGHT/AREA - CHAPTER 5"

(TYPE II B CONSTRUCTION)

ALLOWABLE HEIGHT 3 STORIES ACTUAL HEIGHT 3 STORIES ALLOWABLE AREA, PER FLOOR 23,000 SF ACTUAL AREAS:

- BASEMENT

2,350 SF 2,660 SF 2,820 SF - SECOND - THIRD 2,850 SF

TYPE OF CONSTRUCTION - CHAPTER 6:

(602.2) II B NON-COMBUSTIBLE MATERIALS

TABLE 601 - NO ELEMENTS FOR TYPE II B CONSTRUCTION HAVE FIRE-RESISTANCE

RATING REQUIREMENTS

FIRE RESISTANT CONSTRUCTION - CHAPTER 7

FIRE WALL SEPARATION INTERIOR FINISHES - CHAPTER 8:

CORRIDORS, ROOMS, AND ENCLOSED SPACES CLASS C

6. FIRE PROTECTION SYSTEMS - CHAPTER 9:

NO REQUIREMENTS

OCCUPANCY LOAD:

7,815 SF HABITABLE AREA

HABITABLE AREA / 100 SF PER PERSON (INDUSTRIAL AREAS)= 78 PERSONS OCCUPANT LOAD

HABITABLE AREA / 100 SF PER PERSON (INDUSTRIAL AREAS)= 78 PERSONS OCCUPANT LOAD

MEANS OF EGRESS - CHAPTER 10:

NO REQUIREMENTS

OCCUPANCY LOAD:

HABITABLE AREA 7,815 SF


EXITS REQUIRED


TABLE 1016.1 MAXIMUM EXIT TRAVEL DISTANCE 300 FT

ACTUAL LONGEST TRAVEL DISTANCE

ACCESSIBILITY - CHAPTER 11:


EQUIPMENT AREAS ARE NOT REQUIRED TO BE ACCESSIBLE PER 1103.2





NOTES:

- ATTACH WALLBOARD TO STUDS WITH 1 1/4" LONG TYPE "S" BUGLEHEAD SCREWS AT 12" SPACING. FINISH IN ACCORDANCE WITH ASTM C840 LEVEL 3.
- 2. ATTACH GFRC WITH FLEX ANCHORS AT 2'-0" OC SPACING WITH 5" LEG WELDED TO STUDS WITH (2)-1/2" LONG FLARE BEVEL WELDS AND 4" FOOT ATTACHED TO GFRC WITH 5/8" BONDING PADS THAT EXTEND 2 1/2" BEYOND FOOT EACH SIDE. GFRC HAS 1 1/2" RETURNS PACKED WITH MINERAL FIBER.
- 3. METAL STUD SHALL HAVE A MINIMUM BASE METAL THICKNESS OF 0.060 INCH AND A MINIMUM FLANGE WIDTH OF 1 3/8",AS MANUFACTURED BY DIETRICH METAL FRAMING, OR EQUAL.



DOOR DETAILS

#KEYNOTES:

1. SEE ELECTRICAL DRAWINGS FOR EQUIPMENT 2. PARTITION WALL

GENERAL NOTES:

2. PROVIDE TEMPORARY DUST BARRIERS AND

3. PATCH AND REPAIR ALL FINISHES AT M/E

4. FIELD VERIFY ALL DIMENSIONS.


THE OWNER.

PENETRATIONS.

1. CONTRACTOR SHALL PROTECT ALL EXISTING TO

WEATHER PROOF ENCLOSURES ACCEPTABLE TO

- 3. 1 HOUR FIRE RESISTANT HOLLOW METAL DOOR. IBC
- TABLE 720.1 (2), ITEM 15.1.11.
- 4. FIRE EXTINGUISHER SENTINEL MODEL 10 BY J.L. INDUSTRIES OR EQUAL, SECURELY FASTEN TO STRUCTURE PER MANUFACTURER'S INSTRUCTIONS.



NOT TO SCALE IF THIS DOES NOT MEASURE 1 INCH.



PLAN EL. AT 545.00

SCALE: 1/8"=1'-0"

REVISIONS				ŀ	
NO.	BY	DATE	REMARKS	DES _	SRZ
				DE0 _	
				DWN_	JJH
**************************************				DIII.	
				CKD _	IVC
				0.10	

NORTHERN KENTUCKY WATER DISTRICT TAYLOR MILL WATER TREATMENT PLANT

ELECTRICAL AND BASIN **IMPROVEMENTS**

ARCHITECTURAL


FILTER BUILDING PLAN AT EL 545.00, SECTION AND DETAILS


SCALE: AS NOTED


ISSUED STATUS: BID SET JANUARY 2014

A-01-003

CAD REF. NO. ____A-01-003







CAD REF. NO. 2142001A-01-006

SCALE: AS SHOWN

CKD ___IVC

