

NORTHERN KENTUCKY WATER DISTRICT

PRESIDENT/CEO: - RONALD LOVAN, P.E.	BOARD OF COMMISSIONERS: - DR. PATRICIA SOMMERKAMP - CHAIR - DAVID M. SPAULDING, ESQ - VICE CHAIR - FRED A. MACKE, JR. - SECRETARY - CLYDE CUNNINGHAM - TREASURER - ANDREW C. COLLINS - COMMISSIONER - DOUGLAS C. WAGNER, CDT - COMMISSIONER
VICE PRESIDENTS: - RICHARD B. HARRISON - JACK P. BRAGG, JR.	

Contract Drawings For

Fort Thomas Treatment Plant

Basin Improvements

General/Demolition/Process/ Structural/Electrical

Project No.
000000000218839
HDR-CON0084311

Fort Thomas, Kentucky
January 15, 2015

INDEX OF DRAWINGS

GENERAL

- 00G001 COVER SHEET
- 00G002 LEGEND AND SYMBOLS
- 00G003 CONSTRUCTION STAGING PLAN

DEMOLITION

- 01X101 BASIN #2 FLOCCULATION DEMOLITION PLAN
- 01X102 BASIN #3 FLOCCULATION DEMOLITION PLAN
- 01X103 BASIN #2 CLARIFIER DEMOLITION PLAN
- 01X104 BASIN #3 CLARIFIER DEMOLITION PLAN
- 01X105 RAPID MIX #1 OPERATING FLOOR DEMOLITION PLAN
- 01X106 BASIN #2 AND #3 ELECTRICAL DEMOLITION PHOTO SECTIONS
- 01X301 BASIN #2 AND #3 MISCELLANEOUS DEMOLITION SECTIONS
- 01X302 BASIN #2 AND #3 INFLUENT FLOW CHANNEL DEMOLITION SECTIONS

PROCESS


- 01D101 BASIN #2 FLOCCULATION - LOWER PLAN
- 01D102 BASIN #3 FLOCCULATION - LOWER PLAN
- 01D103 BASIN #2 FLOCCULATION - UPPER PLAN
- 01D104 BASIN #3 FLOCCULATION - UPPER PLAN
- 01D105 BASIN #2 CLARIFIER PLAN
- 01D106 BASIN #3 CLARIFIER PLAN
- 01D107 RAPID MIX #1 FLOOR PLANS
- 01D108 BASIN #2 AND #3 EFFLUENT FLUME TEMPORARY BULKHEAD PLAN
- 01D109 FILTER BUILDING FILTER BAYS PAINT RESTORATION PLAN
- 01D301 BASIN #2 FLOCCULATION - BAFFLE WALL SECTIONS
- 01D302 BASIN #3 FLOCCULATION - BAFFLE WALL SECTIONS
- 01D303 BASIN #2 AND #3 MISCELLANEOUS SECTIONS
- 01D304 BASIN #2 AND #3 MISCELLANEOUS SECTIONS
- 01D305 BASIN #2 AND #3 MISCELLANEOUS SECTIONS
- 01D306 BASIN #2 AND #3 INFLUENT FLOW CHANNEL SECTIONS
- 01D307 BASIN #2 AND #3 MISCELLANEOUS SECTIONS
- 01D501 STANDARD DETAILS
- 01D502 STANDARD DETAILS

STRUCTURAL

- 01S001 GENERAL NOTES
- 01S002 TYPICAL DETAILS
- 01S101 BASIN #2 FLOCCULATION - LOWER PLAN
- 01S102 BASIN #3 FLOCCULATION - LOWER PLAN
- 01S103 BASIN #2 FLOCCULATION - UPPER PLAN
- 01S104 BASIN #3 FLOCCULATION - UPPER PLAN
- 01S105 RAPID MIX PLANS
- 01S106 EXISTING FILTER BLDG. BASEMENT PLANS
- 01D301 BASIN #2 AND #3 FLOCCULATION SECTIONS
- 01D302 BASIN #2 AND #3 FLOCCULATION SECTIONS
- 01D303 BASIN #2 AND #3 FLOCCULATION SECTIONS

ELECTRICAL

- 01E101 INTERIOR ELECTRICAL PLAN
- 01E102 BASIN #2 FLOCCULATION UPPER PLAN
- 01E103 BASIN #3 FLOCCULATION UPPER PLAN
- 01E104 BASIN #2 CLARIFIER PLAN
- 01E105 BASIN #3 CLARIFIER PLAN
- 01E106 PANELBOARD SCHEDULE AND M.C.C. DETAILS
- 01E107 CONTROL SCHEMATICS




VICINITY MAP
NTS

MATERIALS IN PLAN/SECTION

	ACOUSTICAL CEILING TILE (SECTION)
	ASPHALT (PLAN OR SMALL-SCALE SECTION)
	ASPHALT (LARGE-SCALE SECTION)
	BATT INSULATION (SECTION)
	BRICK MASONRY (PLAN AND/OR SECTION)
	CHECKERED PLATE (PLAN)
	CONCRETE (PLAN AND/OR SECTION)
	CONCRETE MASONRY (PLAN AND/OR SECTION)
	DEMOLITION (PLAN AND/OR SECTION)
	EARTH (SECTION)
	GRANULAR FILL (SECTION)
	GRATING (SECTION)
	GRATING (PLAN)
	GROUT (SECTION)
	GYPSUM BOARD (SECTION)
	METAL (SECTION)
	PRECAST CONCRETE (PLAN AND/OR SECTION)
	RIGID INSULATION (SECTION)
	SAND (SECTION)
	WEEP JOINT MORTAR PROTECTION SYSTEM (SECTION)
	HANDRAIL (PLAN) - EXISTING
	HANDRAIL (PLAN) - PROPOSED
	HANDRAIL (SECTION)
	FOAM FILLER (SECTION)

GENERAL SYMBOLOGY



ARCHITECTURAL

ROOM NAME
XX-XX ROOM NUMBER

XXX X DOOR NUMBER

A COLUMN GRID LINE

X WALL TYPE

X WINDOW TYPE

X LOUVER

X ACCESSORY, FURNITURE, AND MISCELLANEOUS EQUIPMENT IDENTIFIER

KEY NOTE DESIGNATION

KEY NOTE NUMBER


GENERAL LINE SYMBOLOGY

--- COLUMN GRID LINE/CENTERLINE

GENERAL ABBREVIATIONS

TYP. EXIST. C. FLOC.	TYPICAL EXISTING CENTERLINE FLOCCULATOR
▽ WSE 780.00	WATER SURFACE ELEVATION
EL. S.S. DIA. ALUM. MAX. MIN. CONC. W/ O.C. VFD M.C.C.	ELEVATION STAINLESS STEEL DIAMETER ALUMINUM MAXIMUM MINIMUM CONCRETE WITH ON CENTER VARIABLE FREQUENCY DRIVE MOTOR CONTROL CENTER

IDENTIFICATION SYMBOLOGY



SHEET NAMING CONVENTION

AREA DESIGNATION
TO BE EDITED ON AN A PROJECT BASIS. TO BE DETERMINED BY THE PROJECT MANAGER, THEN ADDED TO THE GENERAL LEGEND.
EXAMPLE:
01 BUILDING OR AREA NAME
02 BUILDING OR AREA NAME
03 BUILDING OR AREA NAME

DISCIPLINE DESIGNATOR & DISCIPLINE ORDER

G	GENERAL
V	SURVEYING/MAPPING
X	DEMOLITION
C	CIVIL
L	LANDSCAPING
U	MULTI-DISCIPLINE
S	STRUCTURAL
A	ARCHITECTURAL
D	PROCESS
M	MECHANICAL (HVAC)
P	PLUMBING
F	FIRE PROTECTION
E	ELECTRICAL
Y	INSTRUMENTATION

DRAWING TYPE DESIGNATOR

0	GENERAL (SYMBOLS, LEGENDS)
1	PLANS
2	ELEVATIONS
3	SECTIONS
4	LARGE SCALE VIEWS
5	DETAILS
6	SCHEDULES AND DIAGRAMS
8	PROFILES
9	3D REPRESENTATIONS

EXAMPLE
GRAVITY THICKENER ARCHITECTURAL SECTION, SHEET 01

0	5				
---	---	--	--	--	--

AREA DESIGNATION

	A				
--	---	--	--	--	--

DISCIPLINE DESIGNATOR

		3			
--	--	---	--	--	--

SHEET TYPE DESIGNATOR

			0	1	
--	--	--	---	---	--

SHEET NUMBER


* EXCEPTIONS WHERE THE SHEET NUMBER IS REPLACED BY A DASH (-).
1) FOR COMMON DETAILS, SECTIONS, ELEVATIONS OR DETAILS THAT ARE CUT OR CALLED OUT ON MULTIPLE SHEETS.
2) SECTIONS, ELEVATIONS OR DETAILS THAT ARE LOCATED ON THE SAME SHEET THEY ARE CUT OR CALLED OUT ON.

GENERAL NOTES:

1. THIS IS A STANDARD SHEET SHOWING COMMON SYMBOLOGY. ALL SYMBOLS ARE NOT NECESSARILY USED ON THIS PROJECT.

2. SCREENING OR SHADING OF WORK IS USED TO INDICATE EXISTING COMPONENTS OR TO DE-EMPHASIZE PROPOSED IMPROVEMENTS TO HIGHLIGHT SELECTED TRADE WORK. REFER TO CONTEXT OF EACH SHEET FOR USAGE.

PROJECT MANAGER	BRETT D. FISHER
DRAWN BY	B. D. FISHER
REVIEWED BY	P. B. HANSON
DATE	01/15/15
DESCRIPTION	BID SET
PROJECT NUMBER	218839





AERIAL IMAGE TAKEN IN 2012 DURING CONSTRUCTION OF GAC BUILDING AND MISCELLANEOUS SITE IMPROVEMENTS PROJECT. ACTUAL SITE CONDITIONS VARY FROM THOSE DEPICTED IN IMAGE.

PROPOSED SEQUENCE OF WORK

1. MOBILIZE TO SITE
2. INSTALL TEMPORARY FACILITIES
3. PREPARE STAGING AREAS
4. RECEIVE AND PROPERLY STORE CONSTRUCTION MATERIALS
6. INSTALL TEMPORARY BULKHEAD IN COMBINED INFLUENT FLUME FROM BASIN #2 AND #3 TO FILTER BUILDING AS SHOWN ON SHEET 01D108. CONTRACTOR MUST COORDINATE WITH OWNER CLOSELY AS THE ENTIRE PLANT MUST BE TEMPORARILY TAKEN OUT OF SERVICE TO INSTALL TEMPORARY BULKHEAD. PLANT MUST BE DRAINED TO BELOW THE INVERT ELEVATION OF THE INFLUENT FLUME FOR INSTALLATION OF TEMPORARY BULKHEAD. FOLLOWING INSTALLATION, THE PLANT MUST BE PUT BACK INTO SERVICE IMMEDIATELY. THE BULKHEAD SHALL BE FABRICATED OF NSF-61 CERTIFIED MATERIALS. OWNER WILL ALLOW UP TO 4 HOURS OF PLANT SHUTDOWN TO COMPLETE THIS TASK. THE CONTRACTOR SHALL BE PREPARED TO RESTORE PLANT CAPACITY AT ANY TIME AFTER FOUR HOURS IN WHICH THE OWNER REQUESTS. IF THE BULKHEAD IS NOT INSTALLED SUCCESSFULLY ON THE FIRST ATTEMPT, THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAKING UP FOR ANY SCHEDULE DELAYS CAUSED BY ADDITIONAL ATTEMPTS.
7. CONCURRENTLY WITH THE INSTALLATION OF THE TEMPORARY BULKHEAD, THE CONTRACTOR CAN BEGIN REPLACEMENT OF THE 30" INFLUENT BUTTERFLY VALVES UPSTREAM OF RAPID MIX #1 TO FACILITATE DRIP TIGHT SHUT OFF OF INFLUENT RAW WATER FLOW TO RAPID MIX #1. IT IS NOTED THAT RAPID MIX #1 FEEDS BOTH BASIN #2 AND #3. THEREFORE, BOTH BASINS MUST BE TAKEN OUT OF SERVICE WHILE WORK REGARDING THE RAPID MIX #1 AND 30" BUTTERFLY VALVES IS TAKING PLACE.
8. FOLLOWING THE INSTALLATION OF THE TEMPORARY BULKHEAD THE CONTRACTOR CAN REPLACE THE BASIN #2 AND #3 48" EFFLUENT SLIDE GATES. FOLLOWING INSTALLATION, THE TEMPORARY BULKHEAD CAN BE REMOVED.
9. FOLLOWING THE INSTALLATION OF THE 30" BUTTERFLY VALVES AND 48" EFFLUENT SLIDE GATES, THE WORK IN RAPID MIX #1 AND BASIN #2 CAN COMMENCE. THE CONTRACTOR IS NOT PERMITTED TO COMPLETE THE WORK IN BASIN #2 AND #3 CONCURRENTLY AND MUST DO EACH BASIN CONSECUTIVELY. THE CONTRACTOR IS ENCOURAGED TO COMPLETE THE WORK IN RAPID MIX #1 AS QUICKLY AS POSSIBLE SO AS IT CAN BE PUT BACK INTO SERVICE ALONG WITH BASIN #3 TO RESTORE THE PLANT CAPACITY FROM 22 MGD TO 33 MGD UNTIL SUCH A TIME THAT THE BASIN #2 WORK IS COMPLETED.
10. FOLLOWING THE COMPLETION OF THE BASIN #2 WORK AND RECEIVING APPROVAL FROM THE OWNER AND ENGINEER, BASIN #2 CAN BE PUT BACK INTO SERVICE AND WORK CAN COMMENCE ON BASIN #3.
11. COMPLETE ALL MISCELLANEOUS WORK REMAINING, BUT NOT SPECIFICALLY LISTED ABOVE.
12. COMPLETE COMPREHENSIVE CLEANUP OF ENTIRE CONSTRUCTION AREA
13. COMPLETE FINAL PROJECT PUNCHLIST
14. REMOVE PROJECT STAGING AREAS AND RESTORE TO ORIGINAL CONDITION
15. REMOVE TEMPORARY FACILITIES
16. RECEIVE WRITTEN PROJECT ACCEPTANCE FROM OWNER AND ENGINEER
17. DEMOBILIZE FROM SITE

GENERAL NOTES

- REFER TO SECTION 01015 FOR ADDITIONAL REQUIREMENTS AND STIPULATIONS.
- NKWD REQUIRES THE FORT THOMAS TREATMENT PLANT (FTTP) TO BE CAPABLE OF FULL PRODUCTION BETWEEN APRIL 15 AND NOVEMBER 1 OF EACH YEAR. CONTRACTOR SHOULD NOT ANTICIPATE ANY SHUTDOWNS OR REDUCED PLANT CAPACITY DURING THIS PERIOD UNLESS APPROVED IN WRITING BY OWNER.
- CONTRACTOR MUST SUBMIT AN OVERALL MAINTENANCE OF OPERATIONS PLAN (MOP) THAT OUTLINES METHODS, SEQUENCE, AND SCHEDULING FOR THE COMPLETION OF THE PROJECT, AS WELL AS, INDIVIDUAL MOP'S FOR ALL KEY ITEMS OF WORK TO BE REVIEWED AND APPROVED BY OWNER AND ENGINEER PRIOR TO WORK BEING PERFORMED.
- THE PROPOSED CONSTRUCTION SEQUENCING DESCRIBED ON THIS SHEET IS ONLY ONE POTENTIAL SEQUENCING OPTION AND IS GENERAL IN NATURE. THIS SEQUENCING PLAN IS SIMPLY INTENDED TO INFORM THE CONTRACTOR OF MAJOR STAGING CONCERNS THAT NEED TO BE TAKEN INTO ACCOUNT WHEN PREPARING THE MOP FOR THIS PROJECT. THE CONTRACTOR MAY MODIFY THE PROPOSED SEQUENCING ON THIS SHEET AS NECESSARY WITH APPROVAL FROM OWNER AND ENGINEER ON CHANGES.
- AS PART OF THE MOP, CONTRACTOR SHALL ACCOUNT FOR STARTUP TEST PERIODS IN EACH PHASE IN SEQUENCE OF CONSTRUCTION.
- SEVERAL LOCATIONS ON SITE HAVE BEEN DESIGNATED FOR CONSTRUCTION MATERIALS AND EQUIPMENT STAGING AREAS ON THE MAP ON THIS SHEET. NKWD REQUIRES THAT THE CONTRACTOR UTILIZE STAGING AREAS IN THE ORDER IN WHICH THEY ARE NUMBERED. AREA #1 BEING MOST PREFERRED AND AREA #4 BEING LEAST PREFERRED TO BE UTILIZED FOR STAGING.

Northern Kentucky
Water District

**FORT THOMAS TREATMENT PLANT
BASIN IMPROVEMENTS**


**GENERAL
CONSTRUCTION STAGING PLAN**

0 1" 2"
SCALE 1" = 50'

FILENAME 00G003.dwg
SCALE 1" = 50'


SHEET
00G003

**freeland harris
consulting engineers**
201 west short street
suite 410
lexington, kentucky 40507




PROJECT MANAGER BRETT D. FISHER	
DRAWN BY B. D. FISHER	
REVIEWED BY P. B. HANSON	
01/15/15	BID SET
ISSUE	DATE DESCRIPTION
PROJECT NUMBER 218839	






BASIN #2 FLOCCULATION DEMOLITION PLAN
 1/4"=1'-0"




freeland harris consulting engineers
 201 west short street
 suite 410
 lexington, kentucky 40507



PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
DATE		01/15/15
DESCRIPTION		BID SET
PROJECT NUMBER		218839




Northern Kentucky Water District
FORT THOMAS TREATMENT PLANT
BASIN IMPROVEMENTS




DEMOLITION
BASIN #2
FLOCCULATION
DEMOLITION PLAN


FILENAME | 01X101.dwg
 SCALE | 1/4"=1'-0"
 SHEET | **01X101**



BASIN #3 FLOCCULATION DEMOLITION PLAN
 1/4"=1'-0"




freeland harris consulting engineers
 201 west short street
 suite 410
 lexington, kentucky 40507



PROJECT MANAGER	BRETT D. FISHER	
DRAWN BY	B. D. FISHER	
REVIEWED BY	P. B. HANSON	
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER	218839	




Northern Kentucky Water District
FORT THOMAS TREATMENT PLANT
BASIN IMPROVEMENTS



DEMOLITION
BASIN #3
FLOCCULATION
DEMOLITION PLAN


FILENAME | 01X102.dwg
 SCALE | 1/4"=1'-0"

SHEET
01X102





BASIN #2 CLARIFIER DEMOLITION PLAN

3/16"=1'-0"





PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839






BASIN #3 CLARIFIER DEMOLITION PLAN
3/16"=1'-0"




PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839




DEMOLITION BASIN #3 CLARIFIER DEMOLITION PLAN

FILENAME | 01X104.dwg
SCALE | 3/16"=1'-0"
SHEET | **01X104**



RAPID MIX #1 DEMOLITION PLAN
1/4"=1'-0"



PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839






PHOTO 1
BASIN #2 CLAR. ELECTRICAL CONDUIT




PHOTO 2
BASIN #2 CLAR. & FLOC. ELECTRICAL




PHOTO 3
BASIN #2 CLAR. & FLOC. ELECTRICAL



PHOTO 4
BASIN #2 CLAR. & FLOC. ELECTRICAL

- DEMOLITION NOTES:**
- ① REMOVE ALL ELECTRICAL CONDUITS AND MOUNTING HARDWARE.
 - ② REMOVE ALL DISCONNECTS AND CONTROL PANELS.
 - ③ REMOVE FLOCCULATOR DRIVE MOTORS AND ASSEMBLIES.
 - ④ REMOVE UNUSED PANEL BOARD AND PATCH MASONRY WALL AND PAINT TO MATCH SURROUNDING WALL.
 - ⑤ REMOVE LIGHT POLE AND BASE. LEAVE ELECTRICAL JUNCTION FOR CONNECTION OF NEW LIGHT POLE DURING CONSTRUCTION.
 - ⑥ REMOVE BASIN #2 AND #3 FLOCCULATOR VFD UNITS, DISCONNECTS, CONNECTING WIRING, AND CONDUITS BACK TO FEEDING PANEL AND TERMINATE.
 - ⑦ REMOVE EXISTING 6" PLUG VALVE AND ACTUATOR ASSEMBLY, UMBILICAL CORD, AND REMOTE MOUNTED ACTUATOR CONTROLS.




PHOTO 5
BASIN #3 CLAR. & FLOC. ELECTRICAL




PHOTO 6
BASIN #3 CLAR. & FLOC. ELECTRICAL




PHOTO 7
BASIN #3 CLAR. ELECTRICAL CONDUIT




PHOTO 8
RAPID MIX #2 AREA LIGHTING PANEL




PHOTO 12 - BASIN #2 AND #3 (TYPICAL)
6" SLUDGE PLUG VALVE AND ACTUATOR




PHOTO 9
BASIN #2 AND #3 VFDS




PHOTO 11
BASIN #2 CLARIFIER LIGHT POLE




PHOTO 10
BASIN #3 CLARIFIER LIGHT POLE




PHOTO 11 - BASIN #2 AND #3 (TYPICAL)
6" SLUDGE PLUG VALVE ACTUATOR CONTROLS




PROJECT MANAGER	BRETT D. FISHER	
DRAWN BY	R.D. GREER	
REVIEWED BY	R.L. ANDERSON	
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER	218839	




**TYPICAL SECTION
BASINS #2 AND #3 CLARIFIER**
1/4"=1'-0"
(SLUDGE COLLECTION RAKE ROTATED WITH SECTION LINE FOR CLARITY)



**SECTION - SIDE VIEW
BASIN #2 EFFLUENT SLIDE GATE**
1/4"=1'-0"



**TYPICAL SECTION - SIDE VIEW
RAPID MIX BASIN #1**
1/4"=1'-0"




**SECTION - SIDE VIEW
BASIN #3 EFFLUENT SLIDE GATE**
1/4"=1'-0"


**TYPICAL SECTION
BASIN #2 AND #3 FLOCCULATION**
1/4"=1'-0"

PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
ISSUE	DATE	DESCRIPTION
01/15/15	BID SET	
PROJECT NUMBER		218839






SECTION A
1/4"=1'-0"





SECTION B
1/4"=1'-0"

ISSUE	DATE	DESCRIPTION
01/15/15	BID SET	

PROJECT MANAGER	BRETT D. FISHER
DRAWN BY	B. D. FISHER
REVIEWED BY	P. B. HANSON
PROJECT NUMBER	218839









GENERAL NOTES:

1. REPLACE/REINSTALL HANDRAILS, REMOVED DURING DEMO. ALL RAILINGS FORMERLY EMBEDDED POST RAILINGS REMOVED DURING DEMO, SHALL BE REPLACED WITH NEW WALL MOUNTED RAILINGS TO MATCH REMAINDER OF EXISTING RAILINGS WHEN POSSIBLE. IF WALL MOUNT IS NOT POSSIBLE, THEN INSTALL NEW EMBEDDED POST RAILINGS WHERE APPLICABLE. ALL EXISTING RAILINGS DAMAGED DURING DEMOLITION SHALL BE REPLACED WITH NEW RAILINGS OF THE SAME TYPE AND FUNCTION. THE CONTRACTOR MAY OPT TO REPLACE ALL RAILINGS AROUND BASIN #2 AND #3 IN LIEU OF SALVAGING AND REUSING THE EXISTING RAILINGS AS DEPICTED OR IMPLIED ON THE PLANS. CONTRACTOR IS RESPONSIBLE FOR DETERMINING ACTUAL QUANTITIES OF NEW, VS. REINSTALLATION OF EXISTING RAILINGS, BASED ON IT'S PLAN FOR CONSTRUCTION.



BASIN #2 FLOCCULATION – UPPER PLAN
1/4"=1'-0"

freeland harris consulting engineers
201 west short street
suite 410
lexington, kentucky 40507



ISSUE	DATE	DESCRIPTION
01/15/15	BID SET	

PROJECT MANAGER BRETT D. FISHER
DRAWN BY B. D. FISHER
REVIEWED BY P. B. HANSON
PROJECT NUMBER 218839



**FORT THOMAS TREATMENT PLANT
BASIN IMPROVEMENTS**




**PROCESS
BASIN #2
FLOCCULATION
UPPER PLAN**

FILENAME 01D103.wg
SCALE 1/4"=1'-0"

SHEET
01D103



GENERAL NOTES:
 1. REPLACE/REINSTALL HANDRAILS, REMOVED DURING DEMO. ALL RAILINGS FORMERLY EMBEDDED POST RAILINGS REMOVED DURING DEMO, SHALL BE REPLACED WITH NEW WALL MOUNTED RAILINGS TO MATCH REMAINDER OF EXISTING RAILINGS WHEN POSSIBLE. IF WALL MOUNT IS NOT POSSIBLE, THEN INSTALL NEW EMBEDDED POST RAILINGS WHERE APPLICABLE. ALL EXISTING RAILINGS DAMAGED DURING DEMOLITION SHALL BE REPLACED WITH NEW RAILINGS OF THE SAME TYPE AND FUNCTION. THE CONTRACTOR MAY OPT TO REPLACE ALL RAILINGS AROUND BASIN #2 AND #3 IN LIEU OF SALVAGING AND REUSING THE EXISTING RAILINGS AS DEPICTED OR IMPLIED ON THE PLANS. CONTRACTOR IS RESPONSIBLE FOR DETERMINING ACTUAL QUANTITIES OF NEW, VS. REINSTALLATION OF EXISTING RAILINGS, BASED ON IT'S PLAN FOR CONSTRUCTION.



MATCHLINE B-B SEE SHEET 01D103

MATCHLINE C-C SEE SHEET 01D106


BASIN #3 FLOCCULATION - UPPER PLAN
 1/4"=1'-0"



PROJECT MANAGER	BRETT D. FISHER
DRAWN BY	B. D. FISHER
REVIEWED BY	P. B. HANSON
ISSUE	DATE DESCRIPTION
	01/15/15 BID SET
PROJECT NUMBER	218839




**FORT THOMAS TREATMENT PLANT
 BASIN IMPROVEMENTS**




**PROCESS
 BASIN #3
 FLOCCULATION
 UPPER PLAN**

FILENAME | 01D104.dwg
 SCALE | 1/4"=1'-0"
 SHEET | 01D104


GENERAL NOTES:
 1. REPLACE/REINSTALL HANDRAILS, REMOVED DURING DEMO. ALL RAILINGS FORMERLY EMBEDDED POST RAILINGS REMOVED DURING DEMO, SHALL BE REPLACED WITH NEW WALL MOUNTED RAILINGS TO MATCH REMAINDER OF EXISTING RAILINGS WHEN POSSIBLE. IF WALL MOUNT IS NOT POSSIBLE, THEN INSTALL NEW EMBEDDED POST RAILINGS WHERE APPLICABLE. ALL EXISTING RAILINGS DAMAGED DURING DEMOLITION SHALL BE REPLACED WITH NEW RAILINGS OF THE SAME TYPE AND FUNCTION. THE CONTRACTOR MAY OPT TO REPLACE ALL RAILINGS AROUND BASIN #2 AND #3 IN LIEU OF SALVAGING AND REUSING THE EXISTING RAILINGS AS DEPICTED OR IMPLIED ON THE PLANS. CONTRACTOR IS RESPONSIBLE FOR DETERMINING ACTUAL QUANTITIES OF NEW, VS. REINSTALLATION OF EXISTING RAILINGS, BASED ON IT'S PLAN FOR CONSTRUCTION.




BASIN #2 CLARIFIER PLAN
 3/16"=1'-0"



PROJECT MANAGER	BRETT D. FISHER	
DRAWN BY	B. D. FISHER	
REVIEWED BY	P. B. HANSON	
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER	218839	






GENERAL NOTES:

1. REPLACE/REINSTALL HANDRAILS, REMOVED DURING DEMO. ALL RAILINGS FORMERLY EMBEDDED POST RAILINGS REMOVED DURING DEMO, SHALL BE REPLACED WITH NEW WALL MOUNTED RAILINGS TO MATCH REMAINDER OF EXISTING RAILINGS WHEN POSSIBLE. IF WALL MOUNT IS NOT POSSIBLE, THEN INSTALL NEW EMBEDDED POST RAILINGS WHERE APPLICABLE. ALL EXISTING RAILINGS DAMAGED DURING DEMOLITION SHALL BE REPLACED WITH NEW RAILINGS OF THE SAME TYPE AND FUNCTION. THE CONTRACTOR MAY OPT TO REPLACE ALL RAILINGS AROUND BASIN #2 AND #3 IN LIEU OF SALVAGING AND REUSING THE EXISTING RAILINGS AS DEPICTED OR IMPLIED ON THE PLANS. CONTRACTOR IS RESPONSIBLE FOR DETERMINING ACTUAL QUANTITIES OF NEW, VS. REINSTALLATION OF EXISTING RAILINGS, BASED ON IT'S PLAN FOR CONSTRUCTION.

THE PROJECT INTENT IS TO COMPLETE CONSTRUCTION WITH THE TUBE SETTLERS IN PLACE. IT IS THE CONTRACTOR'S RESPONSIBILITY TO AVOID DISTURBING AND DAMAGING THE TUBE SETTLERS WHILE INSTALLING THE NEW SLUDGE COLLECTION SYSTEM. HOWEVER, THE CONTRACTOR MAY OPT TO DISASSEMBLE, REMOVE, AND TEMPORARILY STORE THE TUBE SETTLERS DURING CONSTRUCTION. SEE TECHNICAL SPECIFICATIONS FOR PROPER HANDLING OF TUBE SETTLERS IF NEEDED.

BASIN #3 CLARIFIER PLAN
3/16"=1'-0"




PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839



Northern Kentucky Water District

FORT THOMAS TREATMENT PLANT
BASIN IMPROVEMENTS





PROCESS BASIN #3 CLARIFIER PLAN

FILENAME | 01D106.dwg | SHEET | 01D106


SCALE | 3/16"=1'-0"

freeland harris consulting engineers
201 west short street
suite 410
lexington, kentucky 40507






RAPID MIX #1 LOWER FLOOR PLAN
1/4"=1'-0"




RAPID MIX #1 OPERATING FLOOR PLAN
1/4"=1'-0"




KEY PLAN
NTS

ISSUE	DATE	DESCRIPTION
01/15/15	BID SET	

PROJECT MANAGER	BRETT D. FISHER
DRAWN BY	B. D. FISHER
REVIEWED BY	P. B. HANSON
PROJECT NUMBER	218839






KEY NOTES:


1 REPLACE EXISTING HATCH WITH NEW 44"x47" ALL 316 STAINLESS STEEL FLOOR HATCH AND HARDWARE, BILCO TYPE J-AL OR APPROVED EQUAL. CUT CONCRETE AROUND EXISTING FRAME TO REMOVE EXISTING HATCH AND FRAME, REFORM AND INSTALL NEW FRAME IN CONCRETE/GROUT AS SPECIFIED BY MANUFACTURERS INSTALLATION INSTRUCTIONS FOR "OLD WORK" CONSTRUCTION. FINISHED HATCH INSTALLATION SHALL BE FLUSH WITH EXISTING FLOOR. REPAIR TERRAZZO TILE FLOOR AFTER INSTALLATION. TILE SHALL BE BEST MATCHED FOR COLOR AND TYPE TO THE ADJACENT TILES.

FILTER BUILDING FIRST FLOOR PLAN
BASIN #2 AND #3 EFFLUENT FLUME TEMPORARY BULKHEAD PLAN
 1/8"=1'-0"




PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
ISSUE		DATE
DESCRIPTION		
PROJECT NUMBER		218839





- KEY NOTES:**
- 1 AS PER SPECIFICATIONS SECTION 09906 COMPLETE SURFACE PREPARATION AND PAINT/COAT ALL CEILING, BEAM, AND UPPER 24 INCHES OF WALLS (ABOVE TOP OF WALL TILE) SURFACES WITHIN THE EXTENTS OF THE DESIGNATED BOUNDARIES.
 - 2 CONSTRUCT RIGID PROTECTIVE COVERS OVER ALL FILTERS TO PRECLUDE DEBRIS, PAINT DRIPPINGS, OR OTHER UNWANTED SUBSTANCES FROM ENTERING THE PROCESS WATER OR FILTERS DURING CONSTRUCTION. CONTRACTOR SHALL RECEIVE APPROVAL FROM OWNER ON PROPOSED MEANS OF COVERING OF FILTERS PRIOR TO CONSTRUCTION.
 - 3 SURFACES ABOVE THIS AREA OF THE FILTER BAY ARE IN GOOD CONDITION AND DO NOT NEED TO BE RECOATED AND INCLUDED AS PART OF THE CONTRACTOR'S BID FOR THIS WORK.
 - 4 CONTRACTOR IS REQUIRED TO TEST FOR THE PRESENCE OF LEAD PAINT PRIOR TO BEGINNING WORK AND TAKE THE NECESSARY PRECAUTIONS FOR LEAD PAINT SAFETY IF NEEDED.




**FILTER BUILDING
FILTER BAYS PAINT RESTORATION PLAN**
1/8"=1'-0"




TYPICAL COATING CONDITION
PHOTO 1
NTS



TYPICAL COATING CONDITION
PHOTO 2
NTS






TYPICAL COATING CONDITION
PHOTO 3
NTS




PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839






PROJECT MANAGER	BRETT D. FISHER	
DRAWN BY	B. D. FISHER	
REVIEWED BY	P. B. HANSON	
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER	218839	





SECTION A-A
1/4"=1'-0"
01D102 01D104


SECTION B-B
1/4"=1'-0"
01D102 01D104




SECTION C-C
1/4"=1'-0"
01D102 01D104

PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839






SECTION A-A
1/4"=1'-0"



SECTION B-B
1/4"=1'-0"



PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839




PROCESS BASIN #2 AND #3
MISCELLANEOUS SECTIONS

0 1" 2"

FILENAME 01D303.dwg
SCALE 1/4"=1'-0"


SHEET 01D303

TOP OF CONC. EL. 780.00




SECTION - CLARIFIERS A A
1/4"=1'-0" 01D105 01D106


(RAKE ARM ROTATED PARALLEL TO PLATFORM)




SECTION - FLOCCULATION BASIN B B
1/4"=1'-0" 01D103 01D104



SECTION - RAPID MIX BASIN #1 C
1/4"=1'-0" 01D107



SECTION - RAPID MIX BASIN #1 D
1/4"=1'-0" 01D107




PROJECT MANAGER		BRETT D. FISHER	
DRAWN BY		B. D. FISHER	
REVIEWED BY		P. B. HANSON	
01/15/15	BID SET		
ISSUE	DATE	DESCRIPTION	
			PROJECT NUMBER 218839




**FORT THOMAS TREATMENT PLANT
BASIN IMPROVEMENTS**

**PROCESS
BASIN #2 AND #3
MISCELLANEOUS SECTIONS**




FILENAME 01D304.dwg
SCALE 1/4"=1'-0"


SHEET
01D304




SECTION - EFFLUENT SLIDE GATES
 1/4"=1'-0" A A
 01D105 01D106



BASIN #2 SECTION - EFFLUENT SLIDE GATE
 1/4"=1'-0" B
 01D105




BASIN #3 SECTION - EFFLUENT SLIDE GATE
 1/4"=1'-0" D
 01D106




SECTION - INFLUENT SLIDE GATES
 1/4"=1'-0" C
 01D107

PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839







SECTION
1/4"=1'-0" A A
01D101 01D103



SECTION
1/4"=1'-0" B B
01D102 01D104


ISSUE	DATE	DESCRIPTION	PROJECT NUMBER	218839
	01/15/15	BID SET		
PROJECT MANAGER			BRETT D. FISHER	
DRAWN BY			B. D. FISHER	
REVIEWED BY			P. B. HANSON	






PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839






FRP LADDER DETAIL
3/4"=1'-0"
A
TYP




FRONT VIEW
CONCRETE MOUNTED ALUMINUM HANDRAIL DETAILS
B
TYP


NOTES:
1. ALUMINUM HANDRAIL SHALL BE FABRICATED USING 1 1/2" NOMINAL DIAMETER x 0.145 WALL ALUMINUM PIPE W/WELDED FITTINGS.
2. JOINTS IN RAILING SHALL OCCUR ONLY AT FITTINGS.
3. ALL WELDS SHALL BE GROUND SMOOTH.




FRONT VIEW (LAND SIDE)
PLAN VIEW
HANDRAIL GATE DETAIL INSTALL IN NEW HANDRAIL
C
TYP




END VIEW
HANDRAIL GATE DETAIL INSTALL IN EXISTING HANDRAIL
G
TYP




FRONT VIEW (LAND SIDE)
PLAN VIEW
HANDRAIL GATE DETAIL INSTALL IN EXISTING HANDRAIL
D
TYP



FRONT VIEW
PLAN VIEW
SAFETY CHAIN ACCESS OPENING DETAIL CLOSURE OF EXISTING OPENING
E
TYP




FRONT VIEW
PLAN VIEW
NEW OPENING DETAIL INSTALL IN EXISTING HANDRAIL
F
TYP



SECTION A-A FRONT VIEW


* PROVIDE STEEL CAP FOR POST SLEEVE WHEN BOLLARD IS NOT IN USE

REMOVABLE BOLLARD POST DETAIL (A) TYP NTS



NOTE: SIDEWALK IS TO BE SLOPED TOWARD NATURAL DRAINAGE WHERE APPROPRIATE

CONCRETE SIDEWALK PAVEMENT SECTION (B) TYP NTS



FLOCCULATOR SUPPORT ACCESS WALKWAY BEAM END COPING FOR STEP DETAIL (C) 01D307 NTS

PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		B. D. FISHER
REVIEWED BY		P. B. HANSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839

GENERAL STRUCTURAL NOTES

STRUCTURAL DESIGN CRITERIA

1. THIS STRUCTURE HAS BEEN DESIGNED IN ACCORDANCE WITH THE FOLLOWING DESIGN CODES:
 - A. ACI 350R-06, "ENVIRONMENTAL ENGINEERING CONCRETE STRUCTURES".
 - B. ACI 318-11, "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE".
 - C. KENTUCKY BUILDING CODE, 2013 EDITION.

DESIGN LOADS

ALL BUILDINGS AND STRUCTURES SHALL BE DESIGNED FOR OCCUPANCY CATEGORY III IN ACCORDANCE WITH ASCE 7-10. (TYPICAL UNLESS NOTED)

1. DEAD LOADS
 - A. IN ACCORDANCE WITH THE AMERICAN SOCIETY OF CIVIL ENGINEERS ASCE 7-10, "MINIMUM DESIGN LOADS FOR BUILDINGS AND OTHER STRUCTURES.
2. LIVE LOADS
 - A. THE FOLLOWING LIVE LOADS ARE AS RECOMMENDED IN ACI 350R-06, "ENVIRONMENTAL ENGINEERING CONCRETE STRUCTURES".

CATWALKS AND STAIRS 100 PSF

CAST IN PLACE CONCRETE

1. ALL CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 4500 PSI AT 28 DAYS.
2. ALL DESIGN AND CONSTRUCTION SHALL CONFORM TO THE ACI 318-11 "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE CONSTRUCTION" AND ALL DETAILS SHALL CONFORM TO THE LATEST EDITION OF THE "ACI DETAILING MANUAL" FOR REINFORCED CONCRETE STRUCTURES.
3. THE DESIGN AND CONSTRUCTION OF ALL ENVIRONMENTAL ENGINEERING CONCRETE STRUCTURES SHALL BE IN ACCORDANCE WITH ACI 350R-01, "ENVIRONMENTAL ENGINEERING CONCRETE STRUCTURES".
4. ALL REINFORCING STEEL SHALL BE GRADE 60 DEFORMED TYPE CONFORMING TO ASTM A615.
5. SPLICES IN CONTINUOUS VERTICAL OR HORIZONTAL REINFORCING STEEL SHALL BE CLASS "B" LAP SPLICE UNLESS OTHERWISE NOTED. ALL REINFORCING STEEL SHALL BE CONTINUOUS OR LAPPED WITH DOWELS AT CORNERS.
6. UNLESS OTHERWISE INDICATED, ALL CONCRETE COVER SHALL BE AS FOLLOWS:
 - A. CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH 3"
 - B. CONCRETE CAST WITH FORMS AND EXPOSED TO EARTH, WATER, OR SEWAGE 2"
 - C. ALL OTHER CONCRETE 1 1/2"
7. ALL NON-SHRINK GROUT SHALL BE NON-METALLIC TYPE AND SHALL CONFORM TO CRD-C 621, FACTORY PRE-MIXED.

CRACK REPAIR OF NEW CONCRETE


1. THIS STRUCTURE HAS BEEN DESIGNED TO MINIMIZE CRACKING, PER THE REQUIREMENTS OF ACI 350-06 AND ACI 350.4R-04. THE CONTRACTOR SHOULD CLOSELY FOLLOW THE PROJECT SPECIFICATIONS AND UTILIZE CONSTRUCTION PRACTICES TO MINIMIZE CONCRETE CRACKS.
2. ALL CRACKS THAT ARE ACTIVELY LEAKING OR THOSE WIDER THAN 0.010 INCH THAT OCCUR DURING THE PROJECT WARRANTY PERIOD SHALL BE REPAIRED BY THE CONTRACTOR AT THE CONTRACTOR'S EXPENSE.
3. ALL CRACK REPAIRS SHALL COMPLY WITH THE REQUIREMENTS INCLUDED IN ACI 546R-04, "CONCRETE REPAIR GUIDE" AND ACI 546.3R-06, "GUIDE FOR THE SELECTION OF MATERIALS FOR THE REPAIR OF CONCRETE."
4. THE CONTRACTOR SHALL SUBMIT PROPOSED REPAIR METHODS TO THE STRUCTURAL ENGINEER FOR REVIEW PRIOR TO CONDUCTING ANY REPAIR WORK.

SPECIAL INSPECTIONS:


1. ENGAGING THE SPECIAL INSPECTORS
THE OWNER MUST ENGAGE INSPECTORS TO PERFORM SPECIAL INSPECTION ON THIS PROJECT. THESE INSPECTORS QUALIFICATIONS SHALL BE SUBMITTED TO THE STRUCTURAL ENGINEER FOR CONSIDERATION UPON COMPLETION. ALL REPORTS MUST BE SUBMITTED TO THE STRUCTURAL ENGINEER FOR REVIEW.
2. CONCRETE INSPECTOR REQUIREMENTS
THE SPECIAL CONCRETE INSPECTOR MUST BE AN ACI LEVEL 1 TECHNICIAN.
3. CONCRETE FOUNDATIONS, WALKS AND SLAB ON GRADE.
THE SPECIAL CONCRETE INSPECTOR SHALL INSPECT ALL CONCRETE. THIS INSPECTION SHALL INCLUDE:
 - CONFIRMATION OF ADEQUATE SOIL CONDITION.
 - VERIFICATION OF THE USE OF THE DESIGN MIX.
 - SAMPLE FRESH CONCRETE AS INDICATED IN THE SPECIFICATIONS.
 - VERIFICATION THAT REINFORCEMENT IS AS INDICATED ON THE DRAWINGS AND SPECIFICATIONS.
 - VERIFICATION THAT WATERSTOPS ARE AS SPECIFIED.
4. THE INSPECTION OF MASONRY CONSTRUCTION SHALL INCLUDE:
 - PERIODIC INSPECTIONS OF PROPORTIONS OF SITE-MIXED MORTAR AND GROUT.
 - PERIODIC INSPECTIONS OF PLACEMENT OF MASONRY UNITS AND CONSTRUCTION OF MORTAR JOINTS.
 - PERIODIC INSPECTION OF PLACEMENT OF REINFORCEMENT AND CONNECTORS.
 - CONTINUOUS INSPECTION OF GROUT SPACE CELLS PRIOR TO GROUTING.
 - CONTINUOUS INSPECTION OF THE PLACEMENT OF GROUT.
 - PERIODIC INSPECTION OF SIZE AND LOCATION OF STRUCTURAL ELEMENTS.
 - CONTINUOUS INSPECTION OF TYPE, SIZE AND LOCATION OF ANCHORS, INCLUDING OTHER DETAILS OF ANCHORAGE OF MASONRY TO STRUCTURAL MEMBERS FRAMES OR OTHER CONSTRUCTION.
 - PERIODIC INSPECTION OF SPECIFIED SIZE, GRADE AND TYPE OF REINFORCEMENT.
 - PERIODIC INSPECTION OF PROTECTION OF MASONRY DURING COLD WEATHER (TEMPERATURE BELOW 40°F) AND/OR HOT WEATHER (TEMPERATURE ABOVE 90°F)
 - CONTINUOUS INSPECTION OF PREPARATION OF ANY REQUIRED GROUT SPECIMENS, MORTAR SPECIMENS AND/OR PRISMS SHALL BE OBSERVED.

GENERAL

1. ALL TRADES SHALL REFER ALL APPLICABLE DRAWINGS FOR QUANTITY, LOCATION AND SIZE OF ALL OPENINGS AND EQUIPMENT PENETRATIONS.
2. IT IS THE GENERAL CONTRACTORS RESPONSIBILITY TO COORDINATE ALL OPENING SIZES AND LOCATIONS.
3. ALL CONSTRUCTION JOINTS IN VESSELS TO HAVE WATERSTOPS. PROVIDE EXPANDABLE WATERSTOPS @ EXPANSION JOINTS.
4. ALL WATER STOPS SHALL BE 6" LONG BY 3/8" THICK PVC TYPE, UNLESS NOTED OTHERWISE.




HORIZONTAL CONSTRUCTION JOINT
ELEVATION VIEW




VERTICAL CONSTRUCTION JOINT
PLAN VIEW

TYPICAL CONSTRUCTION JOINTS (S2.1 TYP)




SECTION (S2.4 TYP)




TYPICAL WALL & CORNER INTERSECTION (S2.2 TYP)

NOTE: PROVIDE CONTINUOUS BARS OR DOWELS AT ALL CORNERS AND INTERSECTIONS OF WALLS.




CONNECTION OF NEW WALL TO EXISTING WALL (PERPENDICULAR) (S2.5 TYP)



TYPICAL CONCRETE OPENING DETAIL (S2.3 TYP)

CONCRETE SURFACES REPAIR NOTES AND DETAILS


WALKWAY SURFACE REPAIR



TYPICAL SURFACE SPALLING REPAIR (S2.6 TYP)

ESTIMATED QUANTITIES		
ITEM	QUANTITY	UNITS
OVERALL WALKWAY AREA TO BE REPAIRED	1000	SQUARE FOOT
CRACK REPAIR	150	LF
SPALLED SURFACE AREA REPAIR	200	SQUARE FOOT

BID SHALL BE BASED ON STATED QUANTITIES. QUANTITIES SHALL BE REVIEWED & APPROVED BY OWNER/ENGINEER IN THE FIELD. NO PAYMENT WILL BE MADE FOR UNAPPROVED WORK.




TYPICAL SURFACE SPALLING REPAIR (S2.7 TYP)

WALKWAY SURFACE REPAIR NOTES:

- CHAIN DRAG & IDENTIFY DELAMINATED AREAS
- CHIP AWAY DELAMINATED MATERIAL WITH 15 POUND (MAX.) IMPACT HAMMER
- SQUARE UP DELAMINATED AREA WITH GRINDER TO ELIMINATE FEATHERED EDGES
- SHOT BLAST ENTIRE WALKWAY WITH DUSTLESS SHOT BLASTING EQUIPMENT
- PATCH DELAMINATED AREAS WITH EPOXY (SIKA 22 LOW MOD EPOXY)
- BROADCAST AGGREGATE INTO EPOXY SURFACE
- ROUTE OUT CRACKS WITH 3/8" WIDE V-GROOVE
- SEAL CRACKS WITH SIKA 2C-NS SEALANT
- COAT WALKWAY WITH SIKA FLOOR FTP PRIMER
- COAT WALKWAY WITH SIKALASTIC 720 BASE COAT (25mil.)
- COAT WALKWAY WITH SIKALASTIC 745 AL (12 to 15 mil)
- BROADCAST SURFACE & BACK ROLL WITH ROUNDED QUARTZ AGGREGATE (16 - 30) @ RATE OF 15#/100SQ. OF COATED AREA.

TYPICAL BASIN CRACK REPAIR



TYPICAL CRACK REPAIR (S2.8 TYP)


PLAN/ELEVATION BASIN #2 & #3
ROUTE OUT CRACKS WITH 3/8" WIDE V-GROOVE
INJECT WITH SIKAFIX HH HYDROPHILIC GROUT

BASIN #2 & #3 CRACK REPAIR

- ROUTE OUT CRACKS WITH 3/8" WIDE V-GROOVE.
- INJECT WITH SIKAFLEX HYDROPHILIC GROUT


ESTIMATED QUANTITIES		
ITEM	QUANTITY	UNITS
CRACK REPAIR	3000	LF


BID SHALL BE BASED ON STATED QUANTITIES. QUANTITIES SHALL BE REVIEWED & APPROVED BY OWNER/ENGINEER IN THE FIELD. NO PAYMENT WILL BE MADE FOR UNAPPROVED WORK.



ISSUE	DATE	DESCRIPTION
1/15/15	BID SET	

PROJECT MANAGER	BRETT D. FISHER
DRAWN BY	J.L. HOAGLAND
REVIEWED BY	L.E. ALEXANDER
PROJECT NUMBER	218839







freeland harris
consulting engineers
201 west short street
suite 410
lexington, kentucky 40507



PROJECT MANAGER	BRETT D. FISHER	
DRAWN BY	J.L. HOAGLAND	
REVIEWED BY	L.E. ALEXANDER	
ISSUE	DATE	DESCRIPTION
1/15/15	BID SET	
PROJECT NUMBER	218839	




Northern Kentucky Water District
FORT THOMAS TREATMENT PLANT
BASIN IMPROVEMENTS



**STRUCTURAL
BASIN #3
FLOCCULATION
LOWER PLAN**

FILENAME | 01S102.dwg
SCALE | 1/4"=1'-0"

SHEET
01S102



freeland harris consulting engineers
 201 west short street
 suite 410
 lexington, kentucky 40507




ISSUE	DATE	DESCRIPTION
	1/15/15	BID SET

PROJECT MANAGER BRETT D. FISHER
 DRAWN BY J.L. HOAGLAND
 REVIEWED BY L.E. ALEXANDER
 PROJECT NUMBER 218839





Lyman Edward Alexander

Northern Kentucky Water District
**FORT THOMAS TREATMENT PLANT
 BASIN IMPROVEMENTS**



**STRUCTURAL
 BASIN #2
 FLOCCULATION
 UPPER PLAN**
 FILENAME 01S103.dwg
 SCALE 1/4"=1'-0"

SHEET
01S103



freeland harris consulting engineers
201 west short street
suite 410
lexington, kentucky 40507




ISSUE	DATE	DESCRIPTION
	1/15/15	BID SET


PROJECT MANAGER BRETT D. FISHER
DRAWN BY J.L. HOAGLAND
REVIEWED BY L.E. ALEXANDER
PROJECT NUMBER 218839




Northern Kentucky Water District
FORT THOMAS TREATMENT PLANT
BASIN IMPROVEMENTS




STRUCTURAL
BASIN #3
FLOCCULATION
UPPER PLAN
FILENAME 01S114.dwg
SCALE 1/4"=1'-0"
SHEET
01S104




RAPID MIX #1 LOWER FLOOR PLAN
1/4"=1'-0"




RAPID MIX #1 OPERATING FLOOR PLAN
1/4"=1'-0"



SECTION - RAPID MIX BASIN #1 (A)
1/4"=1'-0"




SECTION - RAPID MIX BASIN #1 (B)
1/4"=1'-0"



ISSUE	DATE	DESCRIPTION
1/15/15	BID SET	

PROJECT MANAGER	BRETT D. FISHER
DRAWN BY	J.L. HOAGLAND
REVIEWED BY	L.E. ALEXANDER
PROJECT NUMBER	218839





EXISTING FILTER BLDG. BASEMENT LOWER FLOOR PLAN

N.T.S.
 - LIMITS OF REPAIR WORK
 - DENOTES ORIGIN & DIRECTION OF PHOTOS

- GENERAL:**
- SOUND ALL CONCRETE WALLS, COLUMNS, BEAMS & CEILING IN AREA A & B.
 - IDENTIFY AND MARK ALL DETERIORATED AREAS TO BE REPAIRED.
 - REMOVE ALL LOOSE AND SCALING PAINT (AREA "B" ONLY).
 - CHIP AWAY DETERIORATED CONCRETE WITH 15 POUND (MAX.) IMPACT HAMMER.
 - REPAIR BEAMS AND CONCRETE SURFACES AS NOTED.
 - CONTRACTOR MUST HAVE AT LEAST 10 YEARS OF EXPERIENCE IN CONCRETE REPAIR METHODS USED.
 - FOLLOW ALL MANUFACTURER'S RECOMMENDATIONS FOR PRODUCTS AND REPAIR PROCEDURES.


- BEAM REPAIR - METHOD A:**
- COAT EXPOSED REINFORCING STEEL WITH SIKA ARMATEC 110 EPOCEM.
 - INSTALL STAINLESS STEEL PINS AND STAINLESS STEEL REINFORCING MAT TO BEAMS.
 - SHOTCRETE BEAMS WITH SIKACEM 103 (1 1/2 TO 2" THICK).

- BEAM REPAIR - METHOD B:**
- CHIP AWAY CONCRETE TO APPROXIMATELY 3" BEYOND EXPOSED REINFORCING STEEL.
 - COAT EXPOSED REINFORCING STEEL WITH SIKA ARMATEC 110 EPOCEM.
 - INSTALL NEW REINFORCING STEEL PER DETAIL B/01S106.
 - FORM AND POUR BEAM ENCASEMENT WITH SIKA MONOTOP 611 POLYMER-MODIFIED MORTAR.

- BEAM REPAIR - METHOD C:**
- CHIP AWAY EXISTING DETERIORATED CONCRETE (NOT LESS THAN 3" BEYOND EXPOSED REINFORCING STEEL).
 - REPLACE EXISTING DETERIORATED REINFORCEMENT PER DETAIL C/01S106.
 - COAT REMAINING EXPOSED REINFORCING STEEL WITH SIKA ARMATEC 110 EPOCEM.
 - FORM AND POUR BEAM REPAIR WITH SIKA MONOTOP 611 POLYMER-MODIFIED MORTAR.

- CEILING REPAIR - METHOD A:**
- COAT EXPOSED REINFORCING STEEL WITH SIKA ARMATEC 110 EPOCEM.
 - INSTALL STAINLESS STEEL PINS AND STAINLESS STEEL REINFORCING MAT TO BOTTOM OF CEILING.
 - SHOTCRETE CEILING WITH SIKACEM 103 (1 1/2 TO 2" THICK).

- WALL AND COLUMNS:**
- COAT EXPOSED REINFORCING STEEL WITH SIKA ARMATEC 110 EPOCEM.
 - PATCH WITH SIKA MONOTOP 611 POLYMER-MODIFIED MORTAR.



SECTION - BEAM REPAIR METHOD B
 3/4"=1'-0"




PHOTO #1 - AREA "A" TYPICAL CONCRETE CONDITION
 N.T.S.
 - PERFORM BEAM REPAIR METHOD A (TYP. AREA "A")



PHOTO #2 - AREA "A" STAIRWAY TYPICAL CONCRETE CONDITION
 N.T.S.
 - PERFORM CEILING REPAIR METHOD A




PHOTO #3 - AREA "B" TYPICAL CONCRETE CONDITION
 N.T.S.
 - PERFORM BEAM REPAIR METHOD B (2 BEAMS IN AREA "B")




SECTION - BEAM REPAIR METHOD C
 3/4"=1'-0"
 REMOVE & REPLACE EXISTING REINFORCEMENT. PROVIDE 24" LAPS, TO EXISTING, TYP.

ESTIMATED QUANTITIES		
ITEM	QUANTITY	UNIT
BEAM REPAIR METHOD A	85	LF
BEAM REPAIR METHOD B	35	LF
BEAM REPAIR METHOD C	15	LF
CEILING REPAIR METHOD A	800	SQUARE FT.
WALL AND COLUMNS	6	EACH (APPROX. 4 SQ. FT. EACH)


BID SHALL BE BASED ON STATED QUANTITIES. QUANTITIES SHALL BE REVIEWED & APPROVED BY OWNER/ENGINEER IN THE FIELD. NO PAYMENT WILL BE MADE FOR UNAPPROVED WORK.



SECTION
 1/4"=1'-0"



SECTION
 1/4"=1'-0"





KEY PLAN
 NTS




ISSUE	DATE	DESCRIPTION
1/15/15	BID SET	

PROJECT MANAGER BRETT D. FISHER
 DRAWN BY J.L. HOAGLAND
 REVIEWED BY L.E. ALEXANDER
 PROJECT NUMBER 218839





FILENAME 01S105.dwg
 SCALE 1/4"=1'-0"
 SHEET 01S106




ISSUE	DATE	DESCRIPTION
1/15/15	BID SET	

PROJECT MANAGER	BRETT D. FISHER
DRAWN BY	J.L. HOAGLAND
REVIEWED BY	L.E. ALEXANDER
PROJECT NUMBER	218839







SECTION 1
1/4"=1'-0"




SECTION 2
1/4"=1'-0"




SECTION 3
3/4"=1'-0"



SECTION 4
3/4"=1'-0"




SECTION A-A
3/4"=1'-0"




SECTION 5
3/4"=1'-0"


ISSUE	DATE	DESCRIPTION
1/15/15	BID SET	

PROJECT MANAGER	BRETT D. FISHER
DRAWN BY	J.L. HOAGLAND
REVIEWED BY	L.E. ALEXANDER
PROJECT NUMBER	218839






SECTION 1
1/4"=1'-0"




SECTION 2
1/4"=1'-0"

ISSUE	DATE	DESCRIPTION
1/15/15	BID SET	

PROJECT MANAGER	BRETT D. FISHER
DRAWN BY	J.L. HOAGLAND
REVIEWED BY	L.E. ALEXANDER
PROJECT NUMBER	218839






MATCHLINE D-D SEE SHEET 01E102

MATCHLINE D-D SEE SHEET 01E103

INTERIOR ELECTRICAL PLAN
1/4" = 1'


- KEY NOTES:**
- ① EQUIPMENT RACK TO BE ATTACHED TO FACE OF EXISTING BUILDING COLUMNS. TOP AND BOTTOM RAILS OF RACK TO BE OF ALUMINUM C-CHANNEL, SIZE AS REQUIRED. PROVIDE TWO VERTICAL C-CHANNEL SUPPORTS ANCHORED TO CONCRETE FLOOR EQUALLY SPACED ON REAR OF RACK. COORDINATE SPACING AND HEIGHT ABOVE FLOOR OF C-CHANNELS TO SUPPORT EQUIPMENT SUPPLIED. USE UNISTRUT VERTICAL MEMBERS AS REQUIRED FOR MOUNTING EQUIPMENT. RACK TO BE CONSTRUCTED TO ACCOMMODATE FUTURE EQUIPMENT, SEE NOTE 2 BELOW.
 - ② SPACE ON REAR OF EQUIPMENT RACK RESERVED FOR FUTURE VFDs AND DISTRIBUTION PANEL FOR BASIN #1 AND #4.
 - ③ VARIABLE FREQUENCY DRIVES FOR BASIN #2 VERTICAL FLOCCULATORS.
 - ④ VARIABLE FREQUENCY DRIVES FOR BASIN #3 VERTICAL FLOCCULATORS.
 - ⑤ REMOVE EXISTING ABANDONED FLUSH MOUNTED PANELBOARD AND DISCONNECT SWITCH. PATCH WALL TO MATCH ADJACENT SURFACES. USE THIS SPACE TO ROUTE ALL CONDUITS TO AND FROM CLARIFIERS AND FLOCCULATORS DOWN WALL. REFER TO PHOTO 8 ON SHEET 01X106.
 - ⑥ CONDUITS TO BASIN #2 FLOCCULATORS AND CLARIFIER. SEE SHEETS 01E102 AND 01E104 FOR CONTINUATION AND FOR NUMBER AND SIZE OF CONDUITS.
 - ⑦ CONDUITS TO BASIN #3 FLOCCULATORS AND CLARIFIER. SEE SHEETS 00E103 AND 00105 FOR CONTINUATION AND FOR NUMBER AND SIZE OF CONDUITS.
 - ⑧ ROUTE CONDUITS THROUGH EXISTING UTILITY VAULT BELOW SIDEWALK.
 - ⑨ CONDUITS TO RACK MOUNTED VFDs, NEW PANELBOARD PP2/3 OR EXISTING PANELBOARD IN MOTOR CONTROL CENTER AS FOLLOWS:
 - FOUR RECEPTACLE/CONTROL CIRCUITS EACH CONNECTED TO SPARE 1-POLE, 20 AMP CIRCUIT BREAKER IN EXISTING MCC PANELBOARD.
 - ONE CLARIFIER LIGHTING CIRCUIT CONNECTED TO SPARE 1-POLE, 20 AMP CIRCUIT BREAKER IN EXISTING MCC PANELBOARD.
 - SIX FLOCCULATOR CIRCUITS AND ASSOCIATED CONTROL WIRING EACH CONNECTED TO RACK MOUNTED VFDs.
 - TWO CLARIFIER CIRCUITS AND ASSOCIATED CONTROL WIRING TO NEW MOTOR STARTERS INSTALLED IN EXISTING MOTOR CONTROL CENTER.
 - TWO EFFLUENT SLIDE GATE CIRCUITS TO NEW PANEL PP2/3.
 SEE PANEL SCHEDULE AND MCC DETAILS SHEET 00E106. COORDINATE EXACT CONDUIT ROUTING IN FIELD.
 - ⑩ FOUR EXISTING FLOCCULATOR VFDs IN THIS LOCATION TO BE REMOVED. DISCONNECT CONDUCTORS AT MOTOR CONTROL CENTER AND REMOVE COMPLETE. REMOVE ALL EXPOSED CONDUIT AND ABANDON CONCEALED CONDUIT IN PLACE. REMOVE FOUR DISCONNECT SWITCHES AND VFDs AND RETURN TO OWNER IN GOOD CONDITION. REFER TO PHOTO 9 ON SHEET 01X106.
 - ⑪ 30 AMP, 3-POLE, NON-FUSED DISCONNECT SWITCH IN NEMA 4X ENCLOSURE.
- GENERAL NOTES:**
1. SEE SHEET 01E106 FOR CIRCUIT CALLOUT SCHEDULE.
 2. SEE SHEET 01E106 FOR PANELBOARD SCHEDULE.




PROJECT MANAGER		BRETT D. FISHER	
DRAWN BY		R.D. GREER	
REVIEWED BY		R.L. ANDERSON	
ISSUE	DATE	DESCRIPTION	PROJECT NUMBER
	01/15/15	BID SET	218839

- KEYNOTES:**
- ① MOUNT ALL EQUIPMENT TO HANDRAIL USING ALL STAINLESS STEEL HARDWARE.
 - ② 30 AMP, 3-POLE, 250 VOLT, NON-FUSED DISCONNECT SWITCH IN NEMA 4X ENCLOSURE, COORDINATE EXACT LOCATION.
 - ③ 60 AMP, 3-POLE, 250 VOLT, NON-FUSED DISCONNECT SWITCH IN NEMA 4X ENCLOSURE, COORDINATE EXACT LOCATION.
 - ④ START/STOP PUSHBUTTON STATION WITH STATUS LIGHTS IN NEMA 4X ENCLOSURE.
 - ⑤ ROUTE ALL CONDUITS BELOW OR ALONG SIDE OF FLOCCULATOR BRIDGE.
 - ⑥ ROUTE CONDUITS ON STAINLESS STEEL CONDUIT SUPPORTS ANCHORED TO SIDE OF CONCRETE WALKWAY.
 - ⑦ TURN CONDUITS DOWN AT FACE OF BASIN WALL, PENETRATE THROUGH SIDEWALK INTO EXISTING UTILITY VAULT BELOW, SEE SHEET 01E101 FOR CONTINUATION.

- GENERAL NOTES:**
- 1. SEE SHEET 01E106 FOR CIRCUIT CALLOUT SCHEDULE.
 - 2. SEE SHEET 01E106 FOR PANELBOARD SCHEDULE.




BASIN #2 FLOCCULATION – UPPER PLAN
1/4"=1'-0"



PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		R.D. GREER
REVIEWED BY		R.L. ANDERSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839

- KEYNOTES:**
- ① MOUNT ALL EQUIPMENT TO HANDRAIL USING ALL STAINLESS STEEL HARDWARE.
 - ② 30 AMP, 3-POLE, 250 VOLT, NON-FUSED DISCONNECT SWITCH IN NEMA 4X ENCLOSURE, COORDINATE EXACT LOCATION.
 - ③ 60 AMP, 3-POLE, 250 VOLT, NON-FUSED DISCONNECT SWITCH IN NEMA 4X ENCLOSURE, COORDINATE EXACT LOCATION.
 - ④ START/STOP PUSHBUTTON STATION WITH STATUS LIGHTS IN NEMA 4X ENCLOSURE.
 - ⑤ ROUTE ALL CONDUITS BELOW OR ALONG SIDE OF FLOCCULATOR BRIDGE.
 - ⑥ ROUTE CONDUITS ON STAINLESS STEEL CONDUIT SUPPORTS ANCHORED TO SIDE OF CONCRETE WALKWAY.
 - ⑦ TURN CONDUITS DOWN AT FACE OF BASIN WALL. PENETRATE THROUGH SIDEWALK INTO EXISTING UTILITY VAULT BELOW, SEE SHEET 01E101 FOR CONTINUATION.

- GENERAL NOTES:**
1. SEE SHEET 01E106 FOR CIRCUIT CALLOUT SCHEDULE.
 2. SEE SHEET 01E106 FOR PANELBOARD SCHEDULE.





MATCHLINE B-B SEE SHEET 01E102

MATCHLINE D-D SEE SHEET 01E101


MATCHLINE C-C SEE SHEET 01E05

CONDUITS FROM CLARIFIER, SEE SHEET 01E104

BASIN #3 FLOCCULATION – UPPER PLAN
1/4"=1'-0"





PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		R.D. GREER
REVIEWED BY		R.L. ANDERSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839



ELECTRICAL BASIN #3 FLOCCULATION UPPER PLAN

FILENAME | 01E103.dwg | SHEET | 01E103

SCALE | 1/4" = 1'-0"




- KEYNOTES:**
- 1 MOUNT ALL EQUIPMENT TO HANDRAIL USING ALL STAINLESS STEEL HARDWARE.
 - 2 CONTROL PANEL PROVIDED WITH EQUIPMENT, INSTALLED BY CONTRACTOR, COORDINATE EXACT LOCATION.
 - 3 30 AMP, 3-POLE, 250 VOLT, NON-FUSED DISCONNECT SWITCH IN NEMA 4X ENCLOSURE, COORDINATE EXACT LOCATION.
 - 4 ROUTE ALL CONDUITS BELOW OR ALONG SIDE OF CLARIFIER BRIDGE.
 - 5 ROUTE CONDUITS ON STAINLESS STEEL CONDUIT SUPPORTS ANCHORED TO SIDE OF CONCRETE WALKWAY.
 - 6 EXISTING 6" PLUG VALVE AND 120 VOLT ELECTRIC ACTUATOR TO BE REPLACED. COORDINATE ELECTRICAL SOURCE, DISCONNECT AND REMOVE EXISTING ACTUATOR. RE-CONNECT NEW ACTUATOR TO EXISTING ELECTRICAL CIRCUIT.

- GENERAL NOTES:**
1. SEE SHEET 01E106 FOR CIRCUIT CALLOUT SCHEDULE.
 2. SEE SHEET 01E106 FOR PANELBOARD SCHEDULE.


BASIN #2 CLARIFIER
MATCHLINE A-A SEE SHEET 01E102

MATCHLINE D-D SEE SHEET 01E105

BASIN #2 CLARIFIER PLAN
3/16" = 1'-0"




freeland harris
consulting engineers
201 west short street
suite 410
lexington, kentucky 40507



PROJECT MANAGER		BRETT D. FISHER
DRAWN BY		R.D. GREER
REVIEWED BY		R.L. ANDERSON
ISSUE	DATE	DESCRIPTION
	01/15/15	BID SET
PROJECT NUMBER		218839




Northern Kentucky
Water District
FORT THOMAS TREATMENT PLANT
BASIN IMPROVEMENTS



ELECTRICAL
BASIN #2
CLARIFIER
PLAN
FILENAME | 01E104.dwg
SCALE | 3/16" = 1'-0"


SHEET
01E104




- KEYNOTES:**
- ① MOUNT ALL EQUIPMENT TO HANDRAIL USING ALL STAINLESS STEEL HARDWARE.
 - ② CONTROL PANEL PROVIDED WITH EQUIPMENT, INSTALLED BY CONTRACTOR, COORDINATE EXACT LOCATION.
 - ③ 30 AMP, 3-POLE, 250 VOLT, NON-FUSED DISCONNECT SWITCH IN NEMA 4X ENCLOSURE, COORDINATE EXACT LOCATION.
 - ④ ROUTE ALL CONDUITS BELOW OR ALONG SIDE OF CLARIFIER BRIDGE.
 - ⑤ ROUTE CONDUITS ON STAINLESS STEEL CONDUIT SUPPORTS ANCHORED TO SIDE OF CONCRETE WALKWAY.
 - ⑥ EXISTING 6" PLUG VALVE AND 120 VOLT ELECTRIC ACTUATOR TO BE REPLACED. COORDINATE ELECTRICAL SOURCE, DISCONNECT AND REMOVE EXISTING ACTUATOR. RE-CONNECT NEW ACTUATOR TO EXISTING ELECTRICAL CIRCUIT.

- GENERAL NOTES:**
1. SEE SHEET 01E106 FOR CIRCUIT CALLOUT SCHEDULE.
 2. SEE SHEET 01E106 FOR PANELBOARD SCHEDULE.

BASIN #3 CLARIFIER PLAN
3/16"=1'-0"




freeland harris consulting engineers
201 west short street
suite 410
lexington, kentucky 40507



PROJECT MANAGER		BRETT D. FISHER	
DRAWN BY		R.D. GREER	
REVIEWED BY		R.L. ANDERSON	
DATE		01/15/15	
ISSUE		DESCRIPTION	
PROJECT NUMBER		218839	



Northern Kentucky Water District
FORT THOMAS TREATMENT PLANT
BASIN IMPROVEMENTS




ELECTRICAL
BASIN #3
CLARIFIER
PLAN

FILENAME | 01E105.dwg
SCALE | 3/16" = 1'-0"


SHEET
01E105

CIRCUIT CALLOUTS

- [A2] = [3/4" CONDUIT, 2-#14]
- [A6] = [3/4" CONDUIT, 6-#14]
- [A12] = [1" CONDUIT, 12-#14]
- [A18] = [1 1/4" CONDUIT, 18-#14]
- [B2] = [3/4" CONDUIT, 2-#12, 1-#12 GROUND]
- [B3] = [3/4" CONDUIT, 3-#12, 1-#12 GROUND]
- [C2] = [3/4" CONDUIT, 2-#10, 1-#10 GROUND]
- [C3] = [3/4" CONDUIT, 3-#10, 1-#10 GROUND]
- [D2] = [3/4" CONDUIT, 2-#8, 1-#8 GROUND]
- [D3] = [1" CONDUIT, 3-#8, 1-#8 GROUND]
- [G2] = [1 1/4" CONDUIT, 2-#3, 1-#8 GROUND]
- [G3] = [1 1/4" CONDUIT, 3-#3, 1-#8 GROUND]
- [J3] = [2" CONDUIT, 3-#1/0, 1-#6 GROUND]
- [J4] = [2" CONDUIT, 4-#1/0, 1-#6 GROUND]




**EXISTING MOTOR CONTROL CENTER
(SQUARE D, MODEL 5)**
NO SCALE




**MODIFIED MOTOR CONTROL CENTER
(SQUARE D, MODEL 5)**
NO SCALE

- KEYNOTES:**
- 1 DISCONNECT AND REMOVE EXISTING RAPID MIX FEEDER COMPLETE. RE-LABEL EXISTING NEMA SIZE 2 STARTER AS SPARE.
 - 2 DISCONNECT AND REMOVE EXISTING CLARIFIER NO. 3 FEEDER COMPLETE. REMOVE EXISTING STARTER COMPLETE AND INSTALL A NEMA SIZE 1 STARTER FOR NEW CLARIFIER NO. 3 IN EXISTING SPACE. REFER TO PHOTOS 5, 6, & 7 ON SHEET 01X106 FOR EXTERIOR CONDUITS.
 - 3 DISCONNECT AND REMOVE EXISTING FLOCC. NO. 3 DRIVES FEEDER COMPLETE. REMOVE EXISTING 70 AMP CIRCUIT COMPLETE. REFER TO PHOTOS 5, 6, & 7 ON SHEET 01X106 FOR EXTERIOR CONDUITS.
 - 4 REMOVE EXISTING LIME BIN DUST COLLECTOR CIRCUIT BREAKER COMPLETE.
 - 5 REMOVE EXISTING FERI FLOCC BIN DUST COLLECTOR CIRCUIT BREAKER COMPLETE.
 - 6 DISCONNECT AND REMOVE EXISTING CLARIFIER NO. 2 FEEDER COMPLETE. REMOVE EXISTING STARTER COMPLETE AND INSTALL A NEMA SIZE 1 STARTER FOR NEW CLARIFIER NO. 2 IN EXISTING SPACE. REFER TO PHOTOS 1, 2, 3, & 4 ON SHEET 01X106 FOR EXTERIOR CONDUITS.
 - 7 DISCONNECT AND REMOVE EXISTING FLOCC. NO. 2 DRIVES FEEDER COMPLETE. RE-LABEL EXISTING 70 AMP CIRCUIT AS SPARE. REFER TO PHOTOS 1, 2, 3, & 4 ON SHEET 01X106 FOR EXTERIOR CONDUITS.
 - 8 EXISTING PANEL LPB TO REMAIN. CONNECT NEW RECEPTACLE AND CONTROL CIRCUITS TO EXISTING SPARE CIRCUIT BREAKERS IN THIS PANEL.
 - 9 INSTALL A NEW 90 AMP, 3-POLE CIRCUIT BREAKER IN EXISTING SPACE FOR 20 HP RAPID MIX VFD.
 - 10 INSTALL A NEW 150 AMP, 3-POLE CIRCUIT BREAKER IN EXISTING SPACE TO FEED PANEL PP2/3.



PANELBOARD		PP2/3	PHASE	3	MOUNTING	Surface	LOCATION	Equipment Rack				
VOLTAGE		208Y/120	WIRE	4		MAIN	MAIN BREAKER	150 Amp, 3-Pole				
CKT #	CB	Wire / Cond.	LOAD SERVED	POLE	VA	LOAD PER PHASE	VA	POLE	LOAD SERVED	Wire / Cond.	CB	CKT #
1	40	#8.1"	BASIN 2 STAGE 1 FLOCCULATOR	1	3039	6078	3039	2	BASIN 3 STAGE 1 FLOCCULATOR	#8.1"	40	2
				3	3039	6078	3039	4				
				5	3039	6078	3039	6				
7	20	#10.3/4"	BASIN 2 STAGE 2 FLOCCULATOR	7	1321	2642	1321	8	BASIN 3 STAGE 2 FLOCCULATOR	#10.3/4"	20	8
				9	1321	2642	1321	10				
				11	1321	2642	1321	12				
13	15	#12.3/4"	BASIN 2 STAGE 3 FLOCCULATOR	13	577	1154	577	14	BASIN 3 STAGE 3 FLOCCULATOR	#12.3/4"	15	14
				15	577	1154	577	16				
				17	577	1154	577	18				
19	15	#12.3/4"	CLARIFIER 2 EFFL. SLIDE GATE	19	421	842	421	20	CLARIFIER 3 EFFL. SLIDE GATE	#12.3/4"	15	20
				21	421	842	421	22				
				23	421	842	421	24				
25	15	#12.3/4"	BASIN 2 RAPID MIX ACTUATOR	25	421	842	421	26	BASIN 3 RAPID MIX ACTUATOR	#12.3/4"	15	26
				27	421	842	421	28				
				29	421	842	421	30				
31	15	#12.3/4"	SPARE	31	500	1000	500	32	SPARE	#12.3/4"	15	32
				33	500	1000	500	34				
				35	500	1000	500	36				
			SPACE ONLY	37	0	0	0	38	SPACE ONLY			
			SPACE ONLY	39	0	0	0	40	SPACE ONLY			
			SPACE ONLY	41	1000	1000	1000	42	SPACE ONLY			
				TOTAL CONNECTED LOAD:		41,774	WATTS					






FLOCCULATOR CONTROL SCHEMATIC - TYPICAL

NOTE:
SCHEMATIC TYPICAL FOR RAPID MIX WITH THE EXCEPTION
THAT IT HAS NO LOCAL START/STOP.



CLARIFIER CONTROL SCHEMATIC - TYPICAL



KEY PLAN
NTS