



ENGINEERED PUMP SERVICES, INC.

624 Perkins Drive · Mukwonago, WI 53149-1454
(262) 363-9002 · (800) 657-0845 · fax (262) 363-9013
www.epspumps.com · email: eps@epspumps.com

CLOSING REPORT

CUSTOMER	: East Kentucky Power Cooperative	REPORT DATE	: 12/22/23
PLANT NAME	: Spurlock Generating Station	REPORT NO.	: 57036-CR1
CITY/STATE	: Maysville, Kentucky	CUST. ORDER	: SP10870
EQUIPMENT	: 06 X 08 X 13 HDB-6 Stage	COPY	: Eddy Meek
SERVICE	: Boiler Feed		
MANF.	: Byron-Jackson	FILE	: 57036
SERIAL NO.	: Element From Unit 1B	PAGE	: 1 of 3

I. SUMMARY OF REPAIRS AND ASSEMBLY

The subject pump arrived at EPS on 10/17/22 for inspection and repair; it was pulled from service after a large vibration spike in fall 2022. As mentioned in the inspection report (57036-IR1), the pump was significantly damaged with many case rings being fused to the impeller turns as well as a bent shaft. It did have the takeoff tube with correct length installed as received. A recommended repair specification and price quotation were submitted on 02/28/23, and approval was received to proceed with the recommended repairs on 05/18/23.

The pump was completely repaired and rebuilt in accordance with EPS specification 57036-RS1; the total indicated runout of the rotating element was under .002", and all floats and lifts measured to acceptable values. Overall, there were no issues with the pump repair or assembly. The completed pump element was returned to Spurlock station on 09/23/23.

Please see the following page of this report for a dimensional summary of all critical fits and clearances. Generally speaking, this element is in the best condition of all three unit #1 feed pumps. It has new a new shaft, chrome plated impeller bores, and impeller turns that have been upgraded with DLD coating. Dimensionally speaking, all critical fits and lengths are very close to OEM specifications.

BY: *Aaron Stull*
Aaron Stull

CLOSING REPORT

CUSTOMER : EKPC - Spurlock
REPORT NO. : 57036-CR1

REPORT DATE : 12/22/23
PAGE : 2 of 3

II. SUMMARY OF FITS AND CLEARANCES							
Impeller, 1 st Stage	Fit Bore	4.2500	4.2505	Series Stage Pieces	Clr. Bore	5.655	5.656
Shaft	Fit Turn	4.2525	4.2530	Series Imp. (hub)	Clr. Turn	5.640	5.641
Resulting Fit		(.0030)	(.0020)	Resulting Clr.		.014	.016
Design Fit		(.0030)	(.0020)	Design Clearance		.014	.016
Impeller, 2 nd & 5 th Stg.	Fit Bore	4.5200	4.5205	1-2 Stage Piece	Clr. Bore	5.859	5.860
Shaft	Fit Turn	4.5225	4.5230	1-2 Stage Sleeve	Clr. Turn	5.844	5.845
Resulting Fit		(.0030)	(.0020)	Resulting Clr.		.014	.016
Design Fit		(.0030)	(.0020)	Design Clearance		.014	.016
Impeller, 3 rd & 6 th Stg.	Fit Bore	4.5250	4.5255	Balance Stage Piece	Clr. Bore	5.292	5.293
Shaft	Fit Turn	4.5275	4.5280	Balance Sleeve	Clr. Turn	5.277	5.278
Resulting Fit		(.0030)	(.0020)	Resulting Clr.		.014	.016
Design Fit		(.0025)	(.0015)	Design Clearance		.014	.016
Impeller, 4 th Stage	Fit Bore	4.5150	4.5155	Casing	Fit Bore	7.787	7.788
Shaft	Fit Turn	4.5175	4.5180	All Wear Rings	Fit Turn	7.785	7.786
Resulting Clr.		(.0030)	(.0020)	Resulting Clr.		.001	.003
Design Clearance		(.0025)	(.0015)	Design Clr.		.001	.003
Series Case Rings	Clr. Bore	6.998	6.999	Casing	Fit Bore	8.787	8.788
Series Impeller (eye)	Clr. Turn	6.983	6.984	Volute Bushing	Fit Turn	8.785	8.786
Resulting Clr.		.014	.016	Resulting Clr.		.001	.003
Design Clearance		.014	.016	Design Clr.		.001	.003
Series Stage Pieces	Clr. Bore	5.655	5.656	TOTAL FLOAT			.320
Series Impeller (hub)	Clr. Turn	5.640	5.641	CE LIFT (0°, 90°)		.015	.016
Resulting Clr.		.014	.016	TE LIFT (0°, 90°)		.021	.023
Design Clearance		.014	.016	PARALLEL LIFTS		.016	.016
1 st Stage Case Ring, CE	Clr. Bore	6.952	6.953				
1 st Stage Impeller, CE	Clr. Turn	6.937	6.938				
Resulting Clr.		.014	.016				
Design Clearance		.014	.016				
Booster Case Ring	Clr. Bore	7.342	7.343				
Booster Impeller (eye)	Clr. Turn	7.327	7.328				
Resulting Clr.		.014	.016				
Design Clearance		.014	.016				
Booster Stage Piece	Clr. Bore	6.170	6.171				
Booster Impeller (hub)	Clr. Turn	6.155	6.156				
Resulting Clr.		.014	.016				
Design Clearance		.014	.016				

CLOSING REPORT

CUSTOMER : EKPC - Spurlock
REPORT NO. : 57036-CR1

REPORT DATE : 12/22/23
PAGE : 3 of 3

Digital Photographs:



Photo 1: Center Impeller Assembly Balance




Photo 2: Trial Fit Of Stationary Rings




Photo 3: Final Assembly



Photo 4: Completed Element In Shipping Crate

Label should be 57036





CEMB



Costruzioni Elettro Meccaniche ing. Buzzi & C. S.p.a.

Balancing Certificate

Customer : XYZ S.p.A	57036	Date : 09/27/2023 04:13:46
Prog. N° 1	57138 rotor balance	
ISO G: 1.00	Total Weight: 540.00 lb	Service Speed: 5600 rpm

	Tol (g)	r (inch)	Dim (inch)	
P1	1.370	6.00	a	32.75
ST	3.132	5.25	b	19.25
P2	1.827	4.50	c	16.62

Initial Unbalances:

P1 (g)	ST (g)	P2 (g)
29.22	48.83	18.05
24.0°	22.7°	19.8°

Residual Unbalances:

P1 (g)	ST (g)	P2 (g)
0.53	1.04	0.62
304.1°	326.8°	352.8°

Measuring speed = 751 rpm

Operator: Rossi Mario

Sign : *Aaron Stull*

NOTES: