

APPENDIX A

UNDERGROUND COST DIFFERENTIAL

A Subdivision of which 113 lots are served Underground.

The line designed at 7.2 KV Primary Voltage, using loop feed:

Underground Cost per Foot	\$12.53
Overhead cost per Foot	<u>3.00</u>
 Average Cost Differential	 \$ <u>9.53</u>

PUBLIC SERVICE COMMISSION
OF KENTUCKY
EFFECTIVE

MAR 1 1989

UNDERGROUND COST COMPUTATION

PURSUANT TO 807 KAR 5:011,
SECTION 9 (1)

BY: *John Miller*
PUBLIC SERVICE COMMISSION MANAGER

	<u>Footage</u>	<u>Material</u>	<u>Estimated: Trench, Sand Backfill Backhoe</u>	<u>Initial Labor & Overhead</u>	<u>Total Cost</u>
Job					
Totals	33,518	\$221,631.39	\$69,294.93	\$129,044.30	\$419,970.62
 Cost per Foot		\$ 6.61	\$ 2.07	\$ 3.85	\$ 12.53

TYPICAL ROCK CLAUSE: An additional \$47.67 per linear trench foot shall be charged where extreme rock conditions are encountered, such conditions being defined as limestone or other hard stratified material in a continuous volume of at least one cubic yard or more which cannot be removed using ordinary excavation equipment.

DATE OF ISSUE: February 17, 1989

DATE EFFECTIVE: March 1, 1989

ISSUED BY *J. Keith Slaw*
SOUTH KENTUCKY R.E.C.C.

P.O. BOX 910

PRESIDENT/GEN. MANAGER
SOMERSET, KENTUCKY 42501

C 9-89