

Louisville Gas and Electric Company

P.S.C. Gas No. 12, Original Sheet No. 99

Terms and Conditions Character of Service

HEATING VALUE

Company will normally supply natural gas having an average heating value of approximately 1,050 Btu per cubic foot for any twelve (12) month period. All gas received into the system of Company from interstate pipelines shall meet the applicable quality standards of the respective interstate pipeline delivering natural gas to Company. All gas received into the system of Company from sources other than an interstate pipeline shall meet the quality standards prescribed in Local Gas Delivery Service Rate LGDS. When it is necessary to supplement the supply of natural gas, Company reserves the right, at its discretion, to supplement its supply of natural gas with a mixture of vaporized liquefied petroleum gas and air.

T
T

STANDARD PRESSURE AND MEASUREMENT BASE

The standard distribution pressure of the gas supplied by Company is four ounces per square inch above atmospheric pressure.

Atmospheric pressure shall be assumed in all cases to be 14.5 pounds per square inch and temperature shall be assumed to be 60 degrees Fahrenheit; provided, however, Company reserves the right for billing purposes to correct as necessary the actual temperature to a 60 degree Fahrenheit basis in the case of large volume customers.

All gas measured at pressures higher than the standard pressure shall be converted to a pressure base of 14.73 pounds per square inch absolute for billing purposes.

DELIVERY PRESSURE

Company shall not be obligated to provide gas service to any Customer at a minimum delivery pressure greater than 50 psig or the expected minimum pipeline pressure, whichever is less.



DATE OF ISSUE: May 14, 2019

DATE EFFECTIVE: Effective with Service Rendered
On And After May 1, 2019

ISSUED BY: /s/ Robert M. Conroy, Vice President
State Regulation and Rates
Louisville, Kentucky

**Issued by Authority of an Order of the
Public Service Commission in Case No.
2018-00295 dated April 30, 2019**

