#### P.S.C. No. 15, Original Sheet No. 57

Standard Rate Rider	NMS	
	Net Metering Service	

APPLICABLE In all territory served.

### AVAILABILITY OF SERVICE

Available to any customer-generator who owns and operates a generating facility located on Customer's premises that generates electricity using solar, wind, biomass or biogas, or hydro energy in parallel with Company's electric distribution system to provide all or part of Customer's electrical requirements, and who executes Company's written Application for Interconnection and Net Metering. The generation facility shall be limited to a maximum rated capacity of 30 kilowatts. This Standard Rate Rider is intended to comply with all provisions of the Interconnection and Net Metering Guidelines approved by the Public Service Commission of Kentucky, which can be found on-line at <u>www.psc.ky.gov</u> as Appendix A to the January 8, 2009 Order in Administrative Case No. 2008-00169.

### METERING AND BILLING

Net metering service shall be measured using a single meter or, as determined by Company, additional meters and shall be measured in accordance with standard metering practices by metering equipment capable of registering power flow in both directions for each time period defined by the applicable rate schedule. This net metering equipment shall be provided without any cost to the Customer. This provision does not relieve Customer's responsibility to pay metering costs embedded in the Company's Commission-approved base rates. Additional meters, requested by Customer, will be provided at Customer's expense.

If electricity generated by Customer and fed back to Company's system exceeds the electricity supplied to Customer from the system during a billing period, Customer shall receive a credit for the net delivery on Customer's bill for the succeeding billing periods. Any such unused excess credits will be carried forward and drawn on by Customer as needed. Unused excess credits existing at the time Customer's service is terminated end with Customer's account and are hold transferrable between customers or locations.

#### NET METERING SERVICE INTERCONNECTION GUIDELINES

## JAN 0 1 2013

ΞD

<u>General</u> – Customer shall operate the generating facility in parallel with Company's systemiunderOMMISSION the following conditions and any other conditions required by Company where unusual circumstances arise not covered herein:

- Customer to own, operate, and maintain all generating facilities on their premises. Such facilities shall include, but not be limited to, necessary control equipment to synchronize frequency, voltage, etc., between Customer's and Company's system as well as adequate protective equipment between the two systems. Customer's voltage at the point of interconnection will be the same as Company's system voltage.
- Customer will be responsible for operating all generating facilities owned by Customer, except as specified hereinafter. Customer will maintain its system in synchronization with Company's system.
- 3. Customer will be responsible for any damage done to Company's equipment due to failure of Customer's control, safety, or other equipment. KENTUCKY
- 4. Customer agrees to inform Company of any changes t wishes to the set of th
- Company will have the right to inspect and approve On stomer's facilities described herein, and to conduct any tests necessary to determine that such facilities are installed and

Date of Issue: August 6, 2010 Date Effective: August 17, 2009 Issued By: Lonnie E. Bellar, Vice President, State Regulation and Rates, Lexington, Kentucky

8/17/2009 PURSUANT TO 807 KAR 5:011 SECTION 9 (1)

Issued by Authority of an Order of the KPSC in Case No. 2009-00548 dated July 30, 2010

#### P.S.C. No. 16, Original Sheet No. 57.1

Standard Rate Rider

#### NMS **Net Metering Service**

#### NET METERING SERVICE INTERCONNECTION GUIDELINES (continued)

operating properly; however, Company will have no obligation to inspect, witness tests, or in any manner be responsible for Customer's facilities or operation thereof.

6. Customer assumes all responsibility for the electric service on Customer's premises at and from the point of delivery of electricity from Company and for the wires and equipment used in connection therewith, and will protect and save Company harmless from all claims for injury or damage to persons or property occurring on Customer's premises or at and from the point of delivery of electricity from Company, occasioned by such electricity or said wires and equipment, except where said injury or damage will be shown to have been occasioned solely by the negligence or willful misconduct of Company.

Level 1 – A Level 1 installation is defined as an inverter-based generator certified as meeting the requirements of Underwriters Laboratories Standard 1741 and meeting the following conditions:

- 1. The aggregated net metering generation on a radial distribution circuit will not exceed 15% of the line section's most recent one hour peak load. A line section is the smallest part of the primary distribution system the generating facility could remain connected to after operation of any sectionalizing devices.
- 2. The aggregated net metering generation on a shared singled-phase secondary will not exceed 20 kVA or the nameplate rating of the service transformer.
- 3. A single-phase net metering generator interconnected on the center tap neutral of a 240 volt service shall not create an imbalance between the two sides of the 240 volt service of more than 20% of the nameplate rating of the service transformer.
- 4. A net metering generator interconnected to Company's three-phase, three-wire primary distribution lines, shall appear as a phase-to-phase connection to Company's primary distribution line.
- 5. A net metering generator interconnected to Company's three-phase, four-wire primary distribution lines, shall appear as an effectively grounded source to Company's primary distribution line.
- 6. A net metering generator will not be connected to an area or spot network.
- 7. There are no identified violations of the applicable provisions of IEEE 1547, "Standard for Interconnecting Distributed Resources with Electric Power Systems".
- 8. Company will not be required to construct any facilities on its own system to accommodate ANCFLLED the net metering generator.

Customer desiring a Level 1 interconnection shall submit a "LEVEL 1 - Application for JAN 0 4 2013 Interconnection and Net Metering." Company shall not the Quetare customer and the second statement of the Customer and Second S Interconnection and Net Metering." Company shall notify Customer within 20 business days asENTUCKY PUBLIC to whether the request is approved or, if denied, the reason(s) for denial. If additionarVICE COMMISSION information is required, the Company will notify Customer, and the time between notification and submission of the information shall not be counted towards the 20 business days. Approval is contingent upon an initial inspection and witness test at the discretion of Company.

Level 2 - A Level 2 installation is defined as generator that is not inverter-based; that uses equipment not certified as meeting the requirements of Underwriters Laboratories Standard 1741. or that does not meet one or more of the conditions required of a Level 1 net metering percentator. A Level 2 Application will be approved if the generating facility me智好的意义。 Interconnection requirements. Those requirements are available on line at 如如此自由我的意义。 upon request. EXECUTIVE DIRECTOR

	TARIEF BRANCH
Date of Issue: January 7, 2013	TAKIM BRANCH
Date Effective: November 1, 2010	D + tike
Issued By: Lonnie E. Bellar, Vice President, State Regula	ation and Rates, LEDun namery
11 00 11.	EFFECTIVE
Nom & Keller	1/1/2013

nome Delle

PURSUANT TO 807 KAR 5:011 SECTION 9 (1) Issued by Authority of an Order of the KPSC in Case Nos. 2009 00548 dated July 30, 2010 and 2010-00204 dated September 30, 2010

### P.S.C. No. 15, First Revision of Original Sheet No. 57.1 Canceling P.S.C. No. 15, Original Sheet No. 57.1

anuart	Rate Rider	NMS Net Metering	Service	
NETM	ETERING SERVICE	INTERCONNECTION GU	IDEL INES (continued)	
	operating properly; h in any manner be re- Customer assumes a from the point of deli in connection therew injury or damage to the point of delivery wires and equipment	however, Company will has sponsible for Customer's f all responsibility for the el ivery of electricity from Co with, and will protect and persons or property occu y of electricity from Comp	ave no obligation to inspect, witness tests, acilities or operation thereof. ectric service on Customer's premises at a mpany and for the wires and equipment us save Company harmless from all claims f rring on Customer's premises or at and fro pany, occasioned by such electricity or sa ury or damage will be shown to have be	nd ed for om aid
requirer 1. 2. 3. 4. 5. 6. 7. 8.	– A Level 1 installat ments of Underwriters The aggregated net of the line section's r the primary distribut operation of any sect The aggregated net exceed 20 kVA or the A single-phase net r volt service shall not more than 20% of the A net metering gene distribution lines, sh distribution lines, sh distribution line. A net metering gener there are no identifier	tion is defined as an inverse Laboratories Standard 17 metering generation on a most recent one hour pea- tion system the generati- tionalizing devices. metering generation on e nameplate rating of the se- metering generator interco- create an imbalance between a metering of the se- metering generator interco- create an imbalance between a metering of the se- erator interconnected to all appear as a phase-to erator will not be connected ed violations of the applic buted Resources with Ele- required to construct any	ter-based generator certified as meeting the 741 and meeting the following conditions: radial distribution circuit will not exceed 15 k load. A line section is the smallest part ng facility could remain connected to aft a shared singled-phase secondary will n service transformer. Onnected on the center tap neutral of a 24 veen the two sides of the 240 volt service service transformer. Company's three-phase, three-wire prima o-phase connection to Company's prima Company's three-phase, four-wire prima ely grounded source to Company's prima to an area or spot network. able provisions of IEEE 1547, "Standard for cric Power Systems".	9% of er ot 40 of ry ry ry ry ry
Inter to w infor and Appr Level 2 equipme or that do Level 2 interconr upon req	<ul> <li>connection and Net Myhether the request mation is required, the submission of the roval is contingent upon – A Level 2 installant not certified as meases not meet one or rapplication will be a nection requirements.</li> </ul>	Metering." Company shall is approved or, if denie he Compary will notify C information shall not be on an initial inspection and ation is defined as gene eeting the requirements o more of the conditions req approved if the generating. Those requirements ar	nall submit a "LEVEL 1 - Application Up notify Customer within 20 business days ad, the reason(s) for denial. If additional ustomer, and the time between notificatio counted towards the 20 business days d witness test at the discretion of Company. rator that is not inverter-based; that use f Underwriters Laboratories Standard 1741 uired of a Level 1 net metering generator. Ing facility meats the Service Scatter of Company e available on line at www.loe-ku.com. DEFF R. DEROUEN EXECUTIVE DIRECTOR TARIFF BRANCH	S S S S S S S S S S S S S S S S S S S
	ve: November 1, 20		ation and Rates, Louiseffective cky	
	Mond Lu	llen	11/1/2010 PURSUANT TO 807 KAR 5:011 SECTION	N 9 (1)

### P.S.C. No. 15, Original Sheet No. 57.2

Standard Rate Rider NMS	
Net Metering Service	
NET METERING SERVICE INTERCONNECTION GUIDELINES (continued)	
Customer desiring a Level 2 interconnection shall submit a "LEVEL 2 - Application for Interconnection and Net Metering." Company shall notify Customer within 30 business days as to whether the request is approved or, if denied, the reason(s) for denial. If additional information is required, the Company will notify Customer, and the time between notification and submission of the information shall not be counted towards the 30 business days. Approval is contingent upon an initial inspection and witness test at the discretion of Company.	
Customer submitting a "Level 2 - Application for Interconnection and Net Metering" will provide a non-refundable inspection and processing fee of \$100, and in the event that the Company determines an impact study to be necessary, shall be responsible for any reasonable costs of up to \$1,000 of documented costs for the initial impact study.	
Additional studies requested by Customer shall be at Customer's expense.	
CONDITIONS OF INTERCONNECTION	
<ul> <li>Customer may operate his net metering generator in parallel with Company's system when complying with the following conditions:</li> <li>1. Customer shall install, operate, and maintain, at Customer's sole cost and expense, any control, protective, or other equipment on Customer's system required by Company's technical interconnection requirements based on IEEE 1547, NEC, accredited testing</li> </ul>	
laboratories, and the manufacturer's suggested practices for safe, efficient and reliable operation of the net metering generating facility in parallel with Company's system. Customer bears full responsibility for the installation, maintenance and safe operation of the net metering generating facility. Upon reasonable request from Company, Customer shall demonstrate compliance.	
<ol> <li>Customer shall represent and warrant compliance of the net metering generator with:</li> <li>any applicable safety and power standards established by IEEE and accredited testing NCEL laboratories;</li> </ol>	
<ul> <li>c) Company's rules and regulations and Terms and Conditions, as may be revised by time-to-time by the Public Service Commission of Kentucky;</li> <li>d) the rules and regulations of the Public Service Commission of Kentucky, as may be revised by time-to-time by the Public Service Commission of Kentucky.</li> </ul>	2013 PUBL MISS
<ul> <li>e) all other local, state, and federal codes and laws, as may be in effect from time-to-time.</li> <li>3. Any changes or additions to Company's system required to accommodate the net metering generator shall be Customer's financial responsibility and Company shall be reimbursed for which shares are different effect.</li> </ul>	
<ul> <li>such changes or additions prior to construction.</li> <li>Customer shall operate the net metering generator in such a manner as not to cause undue fluctuations in voltage, intermittent load characteristics or otherwise interfere with the operation of Company's electric system. Customer shall so operate the generating facility in such a manner that no adverse impacts will be produced thereby to the service quality rendered by Company to any of its other customers or to any electric system interconnected with Company's electric system.</li> </ul>	1
5. Customer shall be responsible for protecting, at Customer's soleBuild States SER VAPERSENTIAL SELON metering generating facility from any condition or disturbance gerecon period departic system, including, but not limited to, voltage sags or svells, system tables of supply, equipment failures, and lighting or switching surges except that the Company shall be responsible for repair of damage caused to the pet metering	-
ate of Issue: August 6, 2010 Bunt Kirtley	
ate Effective: August 17, 2009	1 .
sued By: Lonnie E. Bellar, Vice President, State Regulation and Rates, Lexington, Kentucky 8/17/2009 PURSUANT TO 807 KAR 5:011 SECTION 9 (1)	

Issued by Authority of an Order of the KPSC in Case No. 2009-00548 dated July 30, 2010

P.S.C. No. 15, Original Sheet No. 57.3

	I Rate Rider NMS Net Metering Service
ONDI	ITIONS OF INTERCONNECTION (continued)
	generator resulting solely from the negligence or willful misconduct on the part of the Company.
6.	Following the initial testing and inspection of the generating facility and upon reasonable advance notice to Customer, Company shall have access at reasonable times to the generating facility to perform reasonable on-site inspections to verify that the installation, maintenance and operation of the net metering generator comply with the requirements of this rate schedule.
7.	Where required by the Company, Customer shall furnish and install on Customer's side of the point of interconnection a safety disconnect switch which shall be capable of fully disconnecting Customer's net metering generator from Company's electric service under the full rated conditions of Customer's net metering generator. The external disconnect switch (EDS) shall be located adjacent to Company's meters or the location of the EDS shall be noted by placing a sticker on the meter, and shall be of the visible break type in a metal enclosure which can be secured by a padlock. If the EDS is not located directly adjacent to the meter, Customer shall be responsible for ensuring the location of the EDS
	is properly and legibly identified for so long as the net metering generator is operational. The disconnect switch shall be accessible to Cornpany personnel at all times. Company may waive the requirement for an external disconnect switch for a net metering generator at its sole discretion, and on a case by case basis.
8.	Company shall have the right and authority at Company's sole discretion to isolate the generating facility or require the Customer to discontinue operation of the net metering generator if Company believes that: a) continued interconnection and parallel operation of the net metering generator with
	Company's electric system creates or contributes (or may create or contribute) to a system emergency on either Company's or Customer's electric system; b) the net metering generator is not in compliance with the requirements of this rate
ĸ	schedule, and the non-compliance adversely affects the safety, reliability or power CEL quality of Company's electric system; or c) the net metering generator interferes with the operation of Company's electric system.
	including a description of the specific noncompliance condition and allow Customer a CKY p reasonable time to cure the noncompliance prior to isolating the Generating Facilities. The emergency situations, where the Company is unable to immediately isolate or exact Customer to isolate only the net metering generator, Company may isolate Customer's
9.	entire facility. Customer agrees that, without the prior written permission from Company, no changes shall be made to the generating facility as initially approved. Increases in net metering
	generator capacity will require a new "Application for Interconnection and Net Metering" which will be evaluated on the same basis as any other new application. Repair and replacement of existing generating facility components with like components that meet UL 1741 certification requirements for Level 1 facilities and not resulting in increases in net metering generator capacity is allowed without approval.
10.	Customer shall protect, indemnify and hold harmless Company and its Elizations officers of the contractors against and from all tooss claims.
	actions or suits, including costs and attorneys fees, for or on account of any hill policieath of persons or damage to property caused by Customer or Customer's employees, agents, representatives and contractors in tampering with, repairing, maintaining BANSberating
Effec	tive: August 6, 2010 Eine Bunt Kinking
d By:	E Lonnie E. Bellar, Vice President, State Regulation and Rates, Lexington, Kentucky 8/17/2009 PURSUANT TO 807 KAR 5:011 SECTION 9 (1)
	nomose elle

### P.S.C. No. 15, Original Sheet No. 57.4

andard Rate Ride		NMS et Metering Service		
CONDITIONS OF	INTERCONNECTION (	continued)		
Customer	's net metering generat except where such injur gligence of Company or	or or any related ec ry, death or damage	was caused or co	ntributed to by the
the tariff(s 11. Customer homeown request pr	<ul> <li>The liability of Company to Customer for injury to person and property shall be governed by the tariff(s) for the class of service under which Customer is taking service.</li> <li>11. Customer shall maintain general liability insurance coverage (through a standard homeowner's, commercial or other policy) for generating facilities. Customer shall upon request provide Company with proof of such insurance at the time that application is made for net metering.</li> </ul>			
or by app implied, a as to any	12. By entering into an Interconnection Agreement, or by inspection, if any, or by non-rejection, or by approval, or in any other way, Company does not give any warranty, express or implied, as to the adequacy, safety, compliance with applicable codes or requirements, or as to any other characteristics, of the generating facility equipment, controls, and protective relays and equipment.			
notification compliance being tran installation within 20 Company	13. Customer's generating facility is transferable to other persons or service locations only after notification to the Company has been made and verification that the installation is in compliance with this tariff. Upon written notification that an approved generating facility is being transferred to another person, customer, or location, the Company will verify that the installation is in compliance with this tariff and provide written notification to the customer(s) within 20 business days. If the installation is no longer in compliance with this tariff, the Company will notify Customer in writing and list what must be done to place the facility in compliance.			
	shall retain any and 's generating facilities.	all Renewable Ene	ergy Credits (RE	Cs) generated by
DEFINITIONS "Billing period customer's bill	" shall be the time per Is.	riod between the da	ites on which Co	mpany issues the
electric syster	d Credit" shall be the e m and which exceeds the any billing period.			
TERMS AND CON	NDITIONS			JAN 0 1 2013
Except as pro	vided herein, service w	ill be furnished unde	r Company's Terr	KENTUCKY PUBLIC
applicable her	eto.			RVICE COMMISSION
			JEFF	R. DEROUEN
				RIFF BRANCH
e of Issue: Aug				nt Kirtley
e Effective: Aug	ust 17, 2009 . Bellar, Vice President	. State Regulation a	nd Rates, Lexing	ton, Kentucky
ued By: Lonnie E	- Donar, vice i residen			

andard Rate Rider	NMS
	Net Metering Service
	LEVEL 1
Application for Interconnection and Net Use this application form only for a generating facility meet the requirements of <b>UL</b> 1741.	Metering that is inverter based and certified by a nationally recognized testing laboratory to
Submit this Application to:	
Kentucky Utilities Company, Attn: Cust	tomer Commitment, P. O. Box 32010, Louisville, KY 40232
f you have questions regarding this App	plication or its status, contact KU at:
502-627-2202 (	or customer.commitment@lge-ku.com
Customer Name:	Account Number:
Customer Address:	
Customer Phone No.:	Customer E-mail Address:
Project Contact Person:	
Phone No.:	E-mail Address (Optional):
rovide names and contact information for other stallation of the generating facilities:	contractors, installers, or engineering firms involved in the design and
rovide names and contact information for other stallation of the generating facilities:	contractors, installers, or engineering firms involved in the design and
Provide names and contact information for other installation of the generating facilities:	contractors, installers, or engineering firms involved in the design andHydroBiogasBiomass
Provide names and contact information for other installation of the generating facilities:	contractors, installers, or engineering firms involved in the design andHydroBiogasBiomass
Provide names and contact information for other installation of the generating facilities:	contractors, installers, or engineering firms involved in the design andHydroBiogasBiomass CANCELLEDInverter Voltage Rating:JAN 0 1 2013 s, wind turbine):KENTUCKY PUBLIC
Provide names and contact information for other installation of the generating facilities:	contractors, installers, or engineering firms involved in the design andHydroBiogasBiomassHydroBiogasBiomass CANCELLEDInverter Voltage Rating:JAN 0 1 2013 s, wind turbine):SERVICE COMMISSION
Provide names and contact information for other installation of the generating facilities:	contractors, installers, or engineering firms involved in the design andHydroBiogasBiomassHydroBiogasBiomass CANCELLEDInverter Voltage Rating:JAN 0 1 2013 s, wind turbine):SERVICE COMMISSION
Provide names and contact information for other installation of the generating facilities:	contractors, installers, or engineering firms involved in the design andHydroBiogasBiomass CANCELLEDInverter Voltage Rating:JAN 0 1 2013 s, wind turbine):KENTUCKY PUBLIC SERVICE COMMISSION If Yes, Battery Power Rating:
Provide names and contact information for other installation of the generating facilities:  Inergy Source:SolarWind Inverter Manufacturer and Model #: Inverter Power Rating: Inverter Power Rating: Inverter Power Rating: Inverter Storage Used:NoYes Itach documentation showing that inverter is Equirements of UL 1741. Itach site drawing or sketch showing location of <i>witch</i> ) and inverter. Itach single line drawing showing all electrica cluding switches, fuses, breakers, panels, trar	contractors, installers, or engineering firms involved in the design andHydroBiogasBiomass CANCELLEDInverter Voltage Rating:JAN 0 1 2013 s, wind turbine):KENTUCKY PUBLIC SERVICE COMMISSION If Yes, Battery Power Rating: s certified by a nationally recognized testing laboratory to meet the
Provide names and contact information for other installation of the generating facilities:	contractors, installers, or engineering firms involved in the design and
Provide names and contact information for other installation of the generating facilities:	contractors, installers, or engineering firms involved in the design and
Provide names and contact information for other installation of the generating facilities:  inergy Source:SolarWind inverter Manufacturer and Model #: inverter Power Rating: ower Rating of Energy Source (i.e., solar panels Battery Storage Used:NoYes Itach documentation showing that inverter is equirements of UL 1741. Itach site drawing or sketch showing location of <i>witch</i> ) and inverter. Itach single line drawing showing all electrica	contractors, installers, or engineering firms involved in the design and

P.S.C. No. 15, First Revision of Original Sheet No. 57.6 Canceling P.S.C. No. 15, Original Sheet No. 57.6			
Standard Rate Rider NMS			
Net Metering Service			
LEVEL 2			
Application for Interconnection and Net Metering Use this application form when a generating facility is not inverter-based or is not to meet the requirements of <b>UL</b> 1741 or does not meet any of the additional conditional	certified by a nationally recognized testing laboratory tions under Level 1.		
Submit this Application, along with an application fee of \$100	), to:		
Kentucky Utilities Company, Attn: Customer Commitment, F	P. O. Box 32010, Louisville, KY 40232		
If you have questions regarding this Application or its status,	contact KU at:		
502-627-2202 or customer.commitmer	nt@lge-ku.com		
Customer Name:	Account Number:		
Customer Address:			
Project Contact Person:			
Phone No.: E-mail Address (Optiona			
Provide names and contact information for other contractors, installers, or installation of the generating facilities:	engineering firms involved in the design and		
Total Generating Capacity of Generating Facility:			
Type of Generator:Inverter-BasedSynchronousIn	duction		
Power Source:SolarWindHydro			
Adequate documentation and information must be submitted with this applicatio include the following:	n to be considered complete. Typically this should		
<ol> <li>Single-line diagram of the customer's system showing all electrica interconnection with the Utility's distribution system, including general</li> </ol>	al equipment from the generator to the point of		
tuses, voltage transformers, current transformers, wire sizes, equipment	ratings, and transformer connections. NCELLED		
<ol> <li>Control drawings for relays and breakers.</li> <li>Site Plans showing the physical location of major equipment.</li> </ol>	JAN 0 1 2013		
<ol> <li>Relevant ratings of equipment. Transformer information should in arrangements, and impedance.</li> </ol>	KENTUCKY PUBLIC		
<ol><li>If protective relays are used, settings applicable to the interconnection description of how the relay is programmed to operate as applicable to in</li></ol>	on protection. If programmable relays are used, a structure of the section and		
<ol> <li>A description of how the generator system will be operated including all</li> <li>For inverters, the manufacturer name, model number, and AC power</li> </ol>	modes of operation.		
showing that inverter is certified by a nationally recognized testing laborate	atory to meet the requirements of UL 1741.		
<ol> <li>For synchronous generators, manufacturer and model number, namepla</li> <li>For induction generators, manufacturer and model number, nameplate ratio</li> </ol>	atings, and locked rotor cliffent TUCKY		
	PUBLIC SERVICE COMMISSION		
Customer Signature:	Date: EXECUTIVE DIRECTOR		
Date of Issue: February 2, 2012	TARIFF BRANCH		
Date Effective: November 1, 2010	Bunt Kirtley		
Issued By: Lonnie E. Bellar, Vice President, State Regulation	EFFECTIVE		
Money E Seller	11/1/2010		
issued by Authority of an Order of the KPSC in Case Nos. 2009-0054	PURSUANT TO 807 KAR 5:011 SECTION 9 (1) -slated July 30, 2010 and 2010-00204 dated		
September 30, 2010			

т